

INDUSTRIAL COMPONENT DATA

FRCMM-100/4/003-U 170457 EATON ELECTRIC Circuit breaker, 100A, 4p, 30mA, class Or

Brand: EATON - MOELLER | Manufacturer Part Number: FRCMM-100/4/003-U



Manufacturer	EATON - MOELLER
MPN / Reference	FRCMM-100/4/003-U
Catalog number	170457
Category	Residual current circuit breaker (RCCB)
Minimum order	1 Pcs
Document ID	EO-D7E7FC4D1B
Generated	2026-08-04

Product Overview

Circuit breaker, 100A, 4p, 30mA, class Or

Int. differential FRCMM, 100A, 4p, 30mA, class U

Residual current circuit breaker (RCCB), 100A, 4p, 30mA, type U

Residual current circuit-breaker FRCmM, 4 pole, Rated current I_n : 100 A, Rated short-circuit strength I_{cn} : 10 with back-up fuse kA, Rated fault current $I?N$: 0.03 A, Residual current circuit-breaker - frequency converter-proof

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Industrial

Additional Product Information

Residual current circuit breaker (RCCB), 100A, 4p, 30mA, type U
Residual current circuit-breaker FRCmM, 4 pole, Rated current I_n : 100 A, Rated short-circuit strength I_{cn} : 10 with back-up fuse kA, Rated fault current $I?N$: 0.03 A, Residual current circuit-breaker - frequency converter-proof
Delivery program

Basic function
Residual current circuit-breakers
Number of poles 4 pole
Application Residual current circuit-breaker - frequency converter-proof
Rated current [I_n] 100 A
Rated short-circuit strength [I_{cn}] 10 with back-up fuse kA
Rated fault current [$I?N$] 0.03 A
Type Type U
Tripping Short time-delayed s...
Product range FRCmM
Sensitivity Pulse-current sensitive
Impulse withstand current Surge-proof, 3 kA
Contact sequence
Technical data

Electrical Types conform to IEC/EN 61008
Current test marks As per inscription
Tripping 10 ms delayed s...
Rated voltage according to IEC/EN 60947-2 [U_n] 240/415 V AC
Rated frequency [f] 50/60 Hz
Limit values of the operating voltage Test circuit 196 - 264 V AC
Rated fault current [$I?n$] 30 mA
Sensitivity Pulse-current sensitive
Enhanced sensitivity Suitable for variable frequency drives
Rated insulation voltage [U_i] 440 V
Rated impulse withstand voltage [U_{imp}] 4 (1.2/50us) kV
Rated

short-circuit strength [I_{cn}]10 with back-up fuse kAImpulse withstand current3 kA (8/20 us) surge-proofMax. admissible back-up fuseShort-circuit [gG/gL]100 AMax. admissible back-up fuseOverload [gG/gL]80 ARated making and breaking capacity / Rated residual making and breaking capacity [I_m/ I_m]1000 AlifespanElectrical....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FRCMM-100/4/003-U with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.