

INDUSTRIAL COMPONENT DATA

FRCMM-100/4/03-A-110 180621 Y7-180621 EATON ELECTRIC Residual current circuit breaker (RCCB), 100A, 4p, 300m..

Brand: EATON - MOELLER | Manufacturer Part Number: FRCMM-100/4/03-A-110



Manufacturer	EATON - MOELLER
MPN / Reference	FRCMM-100/4/03-A-110
Catalog number	Y7-180621
Category	Residual current circuit breaker (RCCB)
Minimum order	1 Pcs
Document ID	EO-66FA49E662
Generated	2026-08-06

Product Overview

Residual current circuit breaker (RCCB), 100A, 4p, 300mA, type A, 110V

FRCMM-100/4/03-A-110

Mains voltage-independent residual current circuit-breaker for fault protection and additional protection, 100A, 4p, 300 mA, type A, 110V

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Industrial

Additional Product Information

Residual current circuit breaker (RCCB), 100A, 4p, 300mA, type A, 110V
Mains voltage-independent residual current circuit-breaker for fault protection and additional protection, 100A, 4p, 300 mA, type A, 110V
Delivery program Basic function
Residual current circuit-breakers
Number of poles 4 pole
Application Switchgear for industrial and advanced commercial applications
Rated current [In] 100 A
Rated short-circuit strength [Icn] 10 with back-up fuse kA
Rated fault current [I?N] 0.3 A
Type Type A
Tripping non-delayed s...
Product range FRCmM
Sensitivity Pulse-current sensitive
Impulse withstand current Partly surge-proof 250 A
Technical data
Electrical Types conform to IEC/EN 61008
Current test marks As per inscription
Tripping non-delayed s...
Rated voltage according to IEC/EN 60947-2 [Un] 110/190 V AC
Rated frequency [f] 50/60 Hz
Limit values of the operating voltage Test circuit 94 - 210 V AC
Rated fault current [I?n] 300 mA
Sensitivity Pulse-current sensitive
Rated insulation voltage [Ui] 440 V
Rated impulse withstand voltage [Uimp] 4 (1.2/50us) kV
Rated short-circuit strength [Icn] 10 with back-up fuse kA
Impulse withstand current 250 A (8/20 us) surge-proof
Max. admissible back-up fuse Short-circuit [gG/gL] 100 A
Max. admissible back-up fuse Overload [gG/gL] 80 A
Rated making and breaking capacity / Rated residual making and breaking capacity [Im/

l?m]1000 AlifespanElectrical [Operations]? 4000lifespansMechanical [Operations]? 20000MechanicalStandard front dimension45 mmDevice height80 mmBuilt-in width70 (4TE) mmMountingQuick att...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FRCMM-100/4/03-A-110 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.