

INDUSTRIAL COMPONENT DATA

FRCMM-16/4/01-G 170373 Y7-170373 EATON ELECTRIC

Residual current circuit breaker (RCCB), 16A, 4p, 100mA, typ..

Brand: EATON - MOELLER | Manufacturer Part Number: FRCMM-16/4/01-G



Manufacturer	EATON - MOELLER
MPN / Reference	FRCMM-16/4/01-G
Catalog number	Y7-170373
Category	Residual current circuit breaker (RCCB)
Minimum order	1 Pcs
Document ID	EO-F600E7E040
Generated	2026-08-06

Product Overview

Residual current circuit breaker (RCCB), 16A, 4p, 100mA, type G

Eaton Moeller series xEffect - FRCmM Type AC, A, U, R RCCB. Residual current circuit breaker (RCCB), 16A, 4p, 100mA, type G

Residual current circuit-breaker FRCmM, 4 pole, Rated current I_n : 16 A, Rated short-circuit strength I_{cn} : 10 with back-up fuse kA, Rated fault current I_N : 0.1 A, Switchgear for industrial and advanced commercial applications

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Industrial
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller series xEffect - FRCmM Type AC, A, U, R RCCB Catalog Number 170373 Model Code FRCMM-16/4/01-G EAN 4015081668656 Product Length/Depth 80 mm Product Height 76 mm Product Width 70 mm Product Weight 0.341 kg Compliances RoHS conform Certifications ÖVE E 8601

EN45545-2

IEC 61373

IEC/EN 61008 Delivery program

Application Number of poles Four-pole Tripping time Short time-delayed

10 ms delayed Amperage Rating 16 A Rated short-circuit strength 10 kA with back-up fuse Fault current rating 100 mA

Sensitivity type AC current sensitive Impulse withstand current 3 kA (8/20 us) surge-proof Type Current test marks as per inscription

Maximum operating temperature is 55 °C: Starting at 40 °C, the max. permissible continuous current decreases by 3% for every 1 °C

Technical data - electrical

Voltage rating (IEC/EN 60947-2) 240 V AC / 415 V AC Rated operational voltage (Ue) - max 415 V Rated insulation voltage (Ui) 440 V Rated impulse withstand voltage (Uimp) 4 kV Rated fault current - min 0.1 A Rated fault current - max 0.1 A Frequency rating 50 Hz / 60 Hz Short-circuit rating 63 A (max. admissible back-up fuse) Leakage current type AC Rated residual making and breaking capacity 500 A Admissible back-up fuse overload - max 16 A gG/gL Rated short-time withstand current (Icw) 10 kA Surge current capacity 3 kA Test circuit range 184 V AC - 440 V AC Pollution degree 2 Lifespan, electrical 4000 operations Technical data - mechanical
Frame 45 mm Widt...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FRCMM-16/4/01-G with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.