

INDUSTRIAL COMPONENT DATA

FRCmM-25/2/003-110-GV 304060 Y7-304060 EATON ELECTRIC Supply MIN 30. Differential int. FRCMM, 25A, 2p, 30mA,..

Brand: EATON - MOELLER | Manufacturer Part Number: FRCmM-25/2/003-110-GV



Manufacturer	EATON - MOELLER
MPN / Reference	FRCmM-25/2/003-110-GV
Catalog number	Y7-304060
Category	Residual current circuit breaker (RCCB)
Minimum order	30 Pcs
Document ID	EO-A61DCA0E9C
Generated	2026-08-06

Product Overview

Supply MIN 30. Differential int. FRCMM, 25A, 2p, 30mA, class AC, 110V

FRCmM-25/2/003-110-GV - Residual current circuit breaker (RCCB), 25A 2P 30mA Type AC 110V

Residual current circuit breaker (RCCB), 25A, 2pol, 30mA, Typ AC, 110V, bulk packaging

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog pathEATON - MOELLER > Modular Switchgear - Industrial

Additional Product Information

Residual current circuit breaker (RCCB), 25A 2P 30mA Type AC 110VResidual current circuit breaker (RCCB), 25A, 2pol, 30mA, Typ AC, 110V, bulk packagingDelivery program

Basic functionResidual current circuit-breakersNumber of poles2 poleApplicationSwitchgear for industrial and advanced commercial applicationsRated current [In]25 ARated short-circuit strength [Icn]10 with back-up fuse kARated fault current [I?N]0.03 ATypeType ACTrippingnon-delayed s...Product rangeFRCmMSensitivityAC current sensitiveImpulse withstand currentPartly surge-proof 250 ATechnical data

ElectricalTypes conform toIEC/EN 61008StandardsIEC/EN 61008Current test marksAs per inscriptionTrippingnon-delayed s...Rated voltage according to IEC/EN 60947-2 [Un]110 V ACRated frequency [f]50 HzLimit values of the operating voltageTest circuit94 - 121 V ACRated fault current [I?n]30 mASensitivityAC current sensitiveRated insulation voltage [Ui]440 VRated impulse withstand voltage [Uimp]4 (1.2/50us) kVRated short-circuit strength [Icn]10 with back-up fuse kAImpulse withstand current250 A (8/20 us) surge-proofMax. admissible back-up fuseShort-circuit [gG/gL]63 AMax. admissible back-up fuseOverload [gG/gL]25 ARated making and breaking capacity / Rated residual making and breaking capacity [Im/ I?m]500 AlifespanElectrical [Operations]? 4000lifespanspanMechanical [Operations]? 20000MechanicalStandard

front dimension45 mmDevice height80 mmBuilt-in width35 (2TE) mmMountingQuick attachment with 2 latch positions for DIN-rail IEC/EN...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FRCmM-25/2/003-110-GV with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.