

INDUSTRIAL COMPONENT DATA

FRCMM-25/2/01-S 170315 Y7-170315 EATON ELECTRIC

Residual current circuit breaker (RCCB), 25A, 2p, 100mA, typ..

Brand: EATON - MOELLER | Manufacturer Part Number: FRCMM-25/2/01-S



Manufacturer	EATON - MOELLER
MPN / Reference	FRCMM-25/2/01-S
Catalog number	Y7-170315
Category	Residual current circuit breaker (RCCB)
Minimum order	1 Pcs
Document ID	EO-B3D4A77ED8
Generated	2026-08-06

Product Overview

Residual current circuit breaker (RCCB), 25A, 2p, 100mA, type S

Eaton Moeller series xEffect - FRCmM Type AC, A, U, R RCCB. Residual current circuit breaker (RCCB), 25A, 2p, 100mA, type S

Residual current circuit-breaker FRCmM, 2 pole, Rated current In: 25 A, Rated short-circuit strength Icn: 10 with back-up fuse kA, Rated fault current I_N: 0.1 A, Switchgear for industrial and advanced commercial applications

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Industrial
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller series xEffect - FRCmM Type AC, A, U, R RCCB

Catalog Number 170315

Model Code FRCMM-25/2/01-S

EAN 4015081668120

Product Length/Depth 76 mm

Product Height 80 mm

Product Width 35 mm

Product Weight 0.188 kg

Compliances RoHS conform

Certifications IEC/EN 61008

EN45545-2

IEC 61373

Delivery program

Application Switchgear for industrial and advanced commercial applications

xEffect - Switchgear for industrial and advanced commercial applications

Number of poles Two-pole

Tripping time 40 ms delayed - selective switch off

Selective switch off

Amperage Rating 25 A

Rated short-circuit strength 10 kA with back-up fuse

Fault current rating 100 mA

Sensitivity type AC current sensitive

Impulse withstand current 5 kA (8/20 us) surge-proof

Type FRCmM

Residual current circuit breakers

Type S

Technical Data - Electrical

Voltage rating (IEC/EN 60947-2) 240 V AC

Rated operational voltage (Ue) - max 240 V

Rated insulation voltage (Ui) 440 V

Rated impulse withstand voltage (Uimp) 4 kV

Rated fault current - min 0.1 A

Rated fault current - max 0.1 A

Frequency rating 50 Hz / 60 Hz

Short-circuit rating 63 A (max. admissible back-up fuse)

Leakage current type AC

Rated residual making and breaking capacity 500 A

Admissible back-up fuse overload - max 25 A gG/gL

Rated short-time withstand current (Icw) 10 kA

Surge current capacity 5 kA

Test circuit range 184 V AC - 250 V AC

Pollution degree 2

Lifespan, electrical 4000 operations

Technical Data - Mechanical...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FRCMM-25/2/01-S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.