

INDUSTRIAL COMPONENT DATA

FRCMM-25/4/01-S 170321 Y7-170321 EATON ELECTRIC Circuit breaker, 25A, 4p, 100mA, S-class

Brand: EATON - MOELLER | Manufacturer Part Number: FRCMM-25/4/01-S



Manufacturer	EATON - MOELLER
MPN / Reference	FRCMM-25/4/01-S
Catalog number	Y7-170321
Category	Residual current circuit breaker (RCCB)
Minimum order	1 Pcs
Document ID	EO-1DFAAADAB1
Generated	2026-08-04

Product Overview

Circuit breaker, 25A, 4p, 100mA, S-class

FRCMM-25/4/01-S

Eaton Moeller series xEffect - FRCmM Type AC, A, U, R RCCB. Residual current circuit breaker (RCCB), 25A, 4p, 100mA, type S

Residual current circuit-breaker FRCmM, 4 pole, Rated current I_n : 25 A, Rated short-circuit strength I_{cn} : 10 with back-up fuse kA, Rated fault current I_N : 0.1 A, Switchgear for industrial and advanced commercial applications

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Tertiary and Differential

Additional Product Information

General specifications

Product Name Eaton Moeller series xEffect - FRCmM Type AC, A, U, R RCCB Catalog Number 170321 Model Code FRCMM-25/4/01-S EAN 4015081668175 Product Length/Depth 80 mm Product Height 76 mm Product Width 70 mm Product Weight 0.341 kg Compliances RoHS conform Certifications IEC/EN 61008 EN45545-2

IEC 61373 Delivery program

Application Number of poles Four-pole Tripping time 40 ms delayed - selective switch off

Selective switch off Amperage Rating 25 A Rated short-circuit strength 10 kA with back-up fuse Fault current rating 100 mA

Sensitivity type AC current sensitive Impulse withstand current 5 kA (8/20 us) surge-proof Type FRCmM

Residual current circuit breakers

Type S**Technical data - electrical**

Voltage rating (IEC/EN 60947-2) 240 V AC / 415 V AC Rated operational voltage (Ue) - max 415 V Rated insulation voltage (Ui) 440 V Rated impulse withstand voltage (Uimp) 4 kV Rated fault current - min 0.1 A Rated fault current - max 0.1 A Frequency rating 50 Hz / 60 Hz Short-circuit rating 63 A (max. admissible back-up fuse) Leakage current type AC Rated residual making and breaking capacity 500 A Admissible back-up fuse overload - max 25 A gG/gL Rated short-time withstand current (Icw) 10 kA Surge current capacity 5 kA Test circuit range 184 V AC - 440 V AC Pollution degree 2 Lifespan, electrical 4000 operations Technical data - mechanical
Frame 45 mm Width in number of modular spacings 4 Built-in width (number of units) 70 mm (4 SU) Built-in depth 70.5 mm Moun...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FRCMM-25/4/01-S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.