

INDUSTRIAL COMPONENT DATA

FRCMM-25/4/03-S/A-GV 304059 Y7-304059 EATON ELECTRIC

Supply MIN 15. Differential int. FRCMM, 25A, 4p, 300mA,..

Brand: EATON - MOELLER | Manufacturer Part Number: FRCMM-25/4/03-S/A-GV



Manufacturer	EATON - MOELLER
MPN / Reference	FRCMM-25/4/03-S/A-GV
Catalog number	Y7-304059
Category	Residual current circuit breaker (RCCB)
Minimum order	15 Pcs
Document ID	EO-4968BDC23D
Generated	2026-08-06

Product Overview

Supply MIN 15. Differential int. FRCMM, 25A, 4p, 300mA, class S/A

Residual current circuit breaker (RCCB), 25A 4P 300mA Type S/A

Residual current circuit breaker (RCCB), 25A, 4pol, 300mA, Typ S/A, bulk packaging

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog pathEATON - MOELLER > Modular Switchgear - Tertiary and Differential

Additional Product Information

Residual current circuit breaker (RCCB), 25A 4P 300mA Type S/A
Residual current circuit breaker (RCCB), 25A, 4pol, 300mA, Typ S/A, bulk packaging
Delivery program

Basic functionResidual current circuit-breakersNumber of poles4 poleApplicationSwitchgear for industrial and advanced commercial applicationsRated current [In]25 ARated short-circuit strength [Icn]10 with back-up fuse kARated fault current [I?N]0.3 ATypeType S/ATrippingselective switch off s...Product rangeFRCmMSensitivityPulse-current sensitivelmpulse withstand currentsurge-proof 5 kAContact sequenceTechnical data

ElectricalTypes conform toIEC/EN 61008StandardsIEC/EN 61008Current test marksAs per inscriptionTripping40 ms delay - selective switch off s...Rated voltage according to IEC/EN 60947-2 [Un]240/415 V ACRated frequency [f]50/60 HzLimit values of the operating voltageTest circuit184 - 440 V ACRated fault current [I?n]300 mASensitivityPulse-current sensitivelmpulse withstand voltage [Uimp]4 (1.2/50us) kVRated short-circuit strength [Icn]10 with back-up fuse kAmpulse withstand current5 kA (8/20 us) surge-proofMax. admissible back-up fuseShort-circuit [gG/gL]63 AMax. admissible back-up fuseOverload [gG/gL]25 ARated making and breaking capacity / Rated residual making and breaking capacity [Im/ I?m]500 A lifespanElectrical [Operations]? 4000lifespanMechanical

[Operations]? 20000MechanicalStandard front dimension45 mmDevice height80 mmBuilt-in width70 (4TE)
mmMountingQuick attach...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FRCMM-25/4/03-S/A-GV with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.