

INDUSTRIAL COMPONENT DATA

FRCMM-40/4/01-U 170460 EATON ELECTRIC Residual current circuit breaker (RCCB), 16A, 4p, 100mA, type U

Brand: EATON - MOELLER | Manufacturer Part Number: FRCMM-40/4/01-U



Manufacturer	EATON - MOELLER
MPN / Reference	FRCMM-40/4/01-U
Catalog number	170460
Category	Residual current circuit breaker (RCCB)
Minimum order	1 Pcs
Document ID	EO-E8C94A7036
Generated	2026-08-05

Product Overview

Residual current circuit breaker (RCCB), 16A, 4p, 100mA, type U

Int. differential FRCMM, 40A, 4p, 100mA, class U

Residual current circuit-breaker FRCmM, 4 pole, Rated current I_n : 40 A, Rated short-circuit strength I_{cn} : 10 with back-up fuse kA, Rated fault current I_f : 0.1 A, Residual current circuit-breaker - frequency converter-proof

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Tertiary and Differential

Additional Product Information

General specifications

Product Name Eaton Moeller series xEffect - FRCmM Type AC, A, U, R RCCB Catalog Number 170460 Model Code

FRCMM-40/4/01-U EAN 4015081669448 Product Length/Depth 80 mm Product Height 76 mm Product Width 70 mm

Product Weight 0.344 kg Compliances RoHS conform Certifications IEC/EN 61008 Delivery program

Application Residual current circuit breaker - frequency converter-proof Number of poles Four-pole Tripping time Selective switch off

40 ms delayed - selective switch off Amperage Rating 40 A Rated short-circuit strength 10 kA with back-up fuse Fault current rating 100 mA Sensitivity type Pulse-current sensitive Impulse withstand current 5 kA (8/20 us) surge-proof Type

Technical data - electrical

Voltage rating (IEC/EN 60947-2) 240 V AC / 415 V AC Rated operational voltage (U_e) - max 415 V Rated insulation voltage (U_i) 440 V Rated impulse withstand voltage (U_{imp}) 4 kV

4 kV (1.2/50 μ s) Rated fault current - min 0.1 A Rated fault current - max 0.1 A Frequency rating 50 Hz

50 Hz / 60 Hz Short-circuit rating 63 A (max. admissible back-up fuse) Leakage current type A Rated residual making and breaking capacity 500 A Admissible back-up fuse overload - max 40 A gG/gL Rated short-time withstand current (Icw) 10 kA Surge current capacity 5 kA Test circuit range 196 V AC - 456 V AC Pollution degree 2 Radiation resistance Suitable for variable frequency drives (enhanced sensitivity) Lifespan, electrical 4000 operations Technical data - mechanical Frame 45 mm Width in....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FRCMM-40/4/01-U with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.