

## INDUSTRIAL COMPONENT DATA

**FRCMM-63/4/03-S/A-RT 305111 Y7-305111 EATON ELECTRIC  
Int. Differential FRCMM, 63A, 4p, 300mA, Class S/A Ring..**

Brand: EATON - MOELLER | Manufacturer Part Number: FRCMM-63/4/03-S/A-RT



|                 |                                         |
|-----------------|-----------------------------------------|
| Manufacturer    | EATON - MOELLER                         |
| MPN / Reference | FRCMM-63/4/03-S/A-RT                    |
| Catalog number  | Y7-305111                               |
| Category        | Residual current circuit breaker (RCCB) |
| Minimum order   | 1 Pcs                                   |
| Document ID     | EO-A7666E1826                           |
| Generated       | 2026-08-06                              |

**Product Overview**

Int. Differential FRCMM, 63A, 4p, 300mA, Class S/A Ring Terminal

Eaton Moeller series xEffect - FRCmM-NA RCCB 63A 4P 300mA Type S/A RT

Residual current circuit-breaker FRCmM, 4 Pole, Rated current  $I_n$ : 63 A, Rated short-circuit strength  $I_{cn}$ : 10 with back-up fuse kA, Rated fault current  $I_f$ : 0.3 A, Switchgear for industrial and advanced commercial applications

## STRUCTURED PRODUCT DATA

**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

Catalog path EATON - MOELLER &gt; Modular Switchgear - Tertiary and Differential

**Additional Product Information**

## General specifications

Product Name Eaton Moeller series xEffect - FRCmM-NA RCCB Catalog Number 305111 Model Code

FRCMM-63/4/03-S/A-RT EAN 9010238213838 Product Length/Depth 80 mm Product Height 76 mm Product Width 70 mm

Product Weight 0.32 kg Certifications IEC/EN 61008

EN45545-2

IEC 61373 Delivery program

Application Number of poles Four-pole Amperage Rating 63 A Rated short-circuit strength 10 kA with back-up fuse Fault current rating 300 mA Sensitivity type Pulse-current sensitive Impulse withstand current 5 kA (8/20 us) surge-proof Type FRCmM

Residual current circuit breakers

Type A

Technical data - electrical

Voltage rating (IEC/EN 60947-2) 240 V AC / 415 V AC Rated operational voltage (Ue) - max 415 V Rated insulation voltage (Ui) 440 V Rated impulse withstand voltage (Uimp) 4 kV Rated fault current - min 0.3 A Rated fault current - max 0.3 A Frequency rating 50 Hz / 60 Hz Short-circuit rating 63 A (max. admissible back-up fuse) Leakage current type A Rated residual making and breaking capacity 630 A Admissible back-up fuse overload - max 63 A gG/gL Rated short-time withstand current (Icw) 10 kA Surge current capacity 5 kA Test circuit range 196 V AC - 456 V AC Pollution degree 2 Lifespan, electrical 4000 operations Technical data - mechanical  
Frame 45 mm Width in number of modular spacings 4 Built-in width (number of units) 70 mm (4 SU) Built-in depth 70.5 mm Mounting Method Quick attachment with 2 latch positions for DIN-rail IEC/EN 60715  
DIN rail Mounting position....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FRCMM-63/4/03-S/A-RT with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.