

INDUSTRIAL COMPONENT DATA

FRCMM-80/4/03-G 170380 Y7-170380 EATON ELECTRIC

Residual current circuit breaker (RCCB), 80A, 4p, 300mA, typ..

Brand: EATON - MOELLER | Manufacturer Part Number: FRCMM-80/4/03-G



Manufacturer	EATON - MOELLER
MPN / Reference	FRCMM-80/4/03-G
Catalog number	Y7-170380
Category	Residual current circuit breaker (RCCB)
Minimum order	1 Pcs
Document ID	EO-8F1060F1D5
Generated	2026-08-06

Product Overview

Residual current circuit breaker (RCCB), 80A, 4p, 300mA, type G

Eaton Moeller series xEffect - FRCmM Type AC, A, U, R RCCB. Residual current circuit breaker (RCCB), 80A, 4p, 300mA, type G

Residual current circuit-breaker FRCmM, 4 pole, Rated current I_n: 80 A, Rated short-circuit strength I_{cn}: 10 with back-up fuse kA, Rated fault current I_{ΔN}: 0.3 A, Switchgear for industrial and advanced commercial applications

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Industrial
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller series xEffect - FRCmM Type AC, A, U, R RCCB Catalog Number 170380 Model Code FRCMM-80/4/03-G EAN 4015081668717 Product Length/Depth 80 mm Product Height 76 mm Product Width 70 mm Product Weight 0.381 kg Compliances RoHS conform Certifications ÖVE E 8601

EN45545-2

IEC 61373

IEC/EN 61008 Delivery program

Application Number of poles Four-pole Tripping time 10 ms delayed

Short time-delayed Amperage Rating 80 A Rated short-circuit strength 10 kA with back-up fuse Fault current rating 300 mA

Sensitivity type AC current sensitive Impulse withstand current 3 kA (8/20 us) surge-proof Type FRCmM

Residual current circuit breakers

Type G (ÖVE E 8601)

Technical data - electrical

Voltage rating (IEC/EN 60947-2) 240 V AC / 415 V AC Rated operational voltage (Ue) - max 415 V Rated insulation voltage (Ui) 440 V Rated impulse withstand voltage (Uimp) 4 kV Rated fault current - min 0.3 A Rated fault current - max 0.3 A Frequency rating 50 Hz / 60 Hz Short-circuit rating 80 A (max. admissible back-up fuse) Leakage current type AC Rated residual making and breaking capacity 800 A Admissible back-up fuse overload - max 80 A gG/gL Rated short-time withstand current (Icw) 10 kA Surge current capacity 3 kA Test circuit range 184 V AC - 440 V AC Pollution degree 2 Lifespan, electrical 4000 operations Technical data - mechanical
Frame 45 mm Width in number of modular spacings 4 Built-in width (number of units) 70 mm (4 SU) Built-in depth 70.5 mm Mount...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FRCMM-80/4/03-G with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.