

INDUSTRIAL COMPONENT DATA

DA1-34018FB-A20C 169060 Y7-169060 EATON ELECTRIC

Variable frequency drive, 400 V AC, 3-phase, 18 A, 7.5 kW, ..

Brand: EATON - MOELLER | Manufacturer Part Number: DA1-34018FB-A20C



Manufacturer	EATON - MOELLER
MPN / Reference	DA1-34018FB-A20C
Catalog number	Y7-169060
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-291D1C1518
Generated	2026-08-02

Product Overview

Variable frequency drive, 400 V AC, 3-phase, 18 A, 7.5 kW, IP20/NEMA 0, Radio interference suppression filter, 7-digital display assembly

DA1-34018FB-A20C

Variable frequency drive, Part group reference (e.g. DIL): DA1, Rated operational voltage: $U_e = 400 \text{ V AC}$, 3-phase, 480 V AC, 3-phase, Output voltage with V_e : $U_2 = 400 \text{ V AC}$, 3-phase, 480 V AC, 3-phase, Mains voltage (50/60Hz): $U_{LN} = 380 (-10\%) - 480 (+10\%) \text{ V}$, Rated operational current At 150% overload: $I_e = 18 \text{ A}$, Note: Rated operational current at a switching frequency of 8 kHz and an ambient air temperature of $+50 \text{ }^\circ\text{C}$, Note: Overload cycle for 60 s every 600 s, Assigned motor rating Note: for normal internally and externally ventilated 4 pole, three-phase asynchronous motors with 1500 rpm-1 at 50 Hz or 1800 min-1 at 60 Hz , Overload cycle for 60 s every 600 s, at 400 V, 50 Hz, Assigned motor rating 150 % Overload: $P = 7.5 \text{ kW}$, 150 % Overload: $I_M = 15.2 \text{ A}$, Assigned motor rating Note: at 440 - 480 V, 60 Hz, Assigned motor rating 150 % Overload: $P = 10 \text{ HP}$, Assigned motor rating 150 % Overload: $I_M = 14 \text{ A}$, Degree of Protection: IP20/NEMA 0, Interface/field bus (built-in): OP-Bus (RS485)/Modbus RTU, CANopen®, Fieldbus connection (optional): Ethernet IP, DeviceNet, PROFIBUS, PROFINET, Modbus-TCP, EtherCAT, SmartWire-DT, Fitted with: Radio interference suppression filter, Brake chopper, Additional PCB protection, 7-digital display ass...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Power XL Frequency Converters**

Additional Product Information

General specifications

Product Name Eaton DA1 Variable frequency drive Catalog Number 169060 Model Code DA1-34018FB-A20C EAN

4015081658749 Product Length/Depth 204 mm Product Height 273 mm Product Width 131 mm Product Weight 3.5 kg

Certifications Certified by UL for use in Canada

IEC/EN 61800-3

UL

UL 508C

EAC

IEC/EN61800-3

CUL

UL File No.: E172143

IEC/EN61800-5

Specification for general requirements: IEC/EN 61800-2

RoHS, ISO 9001

Safety: EN 61800-5-1: 2003

UL Category Control No.: NMMS, NMMS7

CE

UkrSEPRO

CSA-C22.2 No. 14

RCM

UL report applies to both US and Canada Catalog Notes The brake resistors are assigned based on the maximum rated power of the variable frequency drive. Additional brake resistors and designs (e.g. different duty cycles) are available upon request. General

Cable length C2 ≤ 5 m, Radio interference level, maximum motor cable length

200 m, screened, with motor choke, maximum permissible, Motor feeder

150 m, unscreened, maximum permissible, Motor feeder

100 m, screened, maximum permissible, Motor feeder

300 m, unscreened, with motor choke, maximum permissible, Motor feeder

C3 ≤ 25 m, Radio interference level, maximum motor cable length Communication interface EtherCAT, optional

SmartWire-DT, optional

CANopen®, built in

Ethernet IP, optional

PROFINET, optional

Modbus RTU, built in

OP-Bus (RS485), built in

Modbus-TCP, optional

DeviceNet, optional

PROFIBUS, optional Connection to SmartWire-DT In conjunction with DX-NET-SWD1 SmartWire DT module

Yes Degree of pr...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DA1-34018FB-A20C with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.