

INDUSTRIAL COMPONENT DATA

DA1-34030FB-B55C 169391 Y7-169391 EATON ELECTRIC

Variable frequency drive, 400 V AC, 3-phase, 30 A, 15 kW, I..

Brand: EATON - MOELLER | Manufacturer Part Number: DA1-34030FB-B55C



Manufacturer	EATON - MOELLER
MPN / Reference	DA1-34030FB-B55C
Catalog number	Y7-169391
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-7344C396FA
Generated	2026-08-04

Product Overview

Variable frequency drive, 400 V AC, 3-phase, 30 A, 15 kW, IP55/NEMA 12, Radio interference suppression filter, OLED display

DA1-34030FB-B55C

Variable frequency drive, Part group reference (e.g. DIL): DA1, Rated operational voltage: $U_e = 400 \text{ V AC}$, 3-phase, 480 V AC, 3-phase, Output voltage with V_e : $U_2 = 400 \text{ V AC}$, 3-phase, 480 V AC, 3-phase, Mains voltage (50/60Hz): $U_{LN} = 380 (-10\%) - 480 (+10\%) \text{ V}$, Rated operational current At 150% overload: $I_e = 30 \text{ A}$, Note: Rated operational current at a switching frequency of 8 kHz and an ambient air temperature of $+40^\circ \text{C}$, Note: Overload cycle for 60 s every 600 s, Assigned motor rating Note: for normal internally and externally ventilated 4 pole, three-phase asynchronous motors with 1500 rpm-1 at 50 Hz or 1800 min-1 at 60 Hz , Overload cycle for 60 s every 600 s, at 400 V, 50 Hz, Assigned motor rating 150 % Overload: $P = 15 \text{ kW}$, 150 % Overload: $I_M = 29.3 \text{ A}$, Assigned motor rating Note: at 440 - 480 V, 60 Hz, Assigned motor rating 150 % Overload: $P = 20 \text{ HP}$, Assigned motor rating 150 % Overload: $I_M = 27 \text{ A}$, Degree of Protection: IP55/NEMA 12, Interface/field bus (built-in): OP-Bus (RS485)/Modbus RTU, CANopen®, Fieldbus connection (optional): Ethernet IP, DeviceNet, PROFIBUS, PROFINET, Modbus-TCP, EtherCAT, SmartWire-DT, Fitted with: Radio interference suppression filter, Brake chopper, Additional PCB protection, OLED display, Frame size: FS4 , Sta...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Power XL Frequency Converters**

Additional Product Information

General specifications

Product Name Eaton DA1 Variable frequency drive Catalog Number 169391 Model Code DA1-34030FB-B55C EAN

4015081658343 Product Length/Depth 240 mm Product Height 450 mm Product Width 173 mm Product Weight 11.5 kg

Certifications UL report applies to both US and Canada

IEC/EN61800-3

CE

CSA-C22.2 No. 14

Certified by UL for use in Canada

CUL

EAC

IEC/EN61800-5

UL Category Control No.: NMMS, NMMS7

RoHS, ISO 9001

DNV

UL 508C

RCM

UkrSEPRO

UL File No.: E172143

IEC/EN 61800-3

Specification for general requirements: IEC/EN 61800-2

UL

Safety: EN 61800-5-1: 2003 Catalog Notes The brake resistors are assigned based on the maximum rated power of the variable frequency drive. Additional brake resistors and designs (e.g. different duty cycles) are available upon request.

General

Cable length C2 ≤ 5 m, Radio interference level, maximum motor cable length

C3 ≤ 25 m, Radio interference level, maximum motor cable length

100 m, screened, maximum permissible, Motor feeder

150 m, unscreened, maximum permissible, Motor feeder

200 m, screened, with motor choke, maximum permissible, Motor feeder

300 m, unscreened, with motor choke, maximum permissible, Motor feeder Communication interface DeviceNet, optional

Modbus-TCP, optional

EtherCAT, optional

SmartWire-DT, optional

OP-Bus (RS485), built in

PROFIBUS, optional

CANopen®, built in

Modbus RTU, built in

Ethernet IP, optional

PROFINET, optional Connection to SmartWire-DT In conjunction with DX-NET-SWD1 SmartWire DT module

Yes Degree....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DA1-34030FB-B55C with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.