

INDUSTRIAL COMPONENT DATA

DA1-34202FB-B55C 169405 Y7-169405 EATON ELECTRIC

Variable frequency drive, 400 V AC, 3-phase, 202 A, 110 kW,..

Brand: EATON - MOELLER | Manufacturer Part Number: DA1-34202FB-B55C



Manufacturer	EATON - MOELLER
MPN / Reference	DA1-34202FB-B55C
Catalog number	Y7-169405
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-E6422CFE5D
Generated	2026-08-04

Product Overview

Variable frequency drive, 400 V AC, 3-phase, 202 A, 110 kW, IP55/NEMA 12, Radio interference suppression filter, OLED display, DC link choke

DA1-34202FB-B55C

Variable frequency drive, Part group reference (e.g. DIL): DA1, Rated operational voltage: $U_e = 400$ V AC, 3-phase, 480 V AC, 3-phase, Output voltage with V_e : $U_2 = 400$ V AC, 3-phase, 480 V AC, 3-phase, Mains voltage (50/60Hz): $U_{LN} = 380$ (-10%) - 480 (+10%) V, Rated operational current At 150% overload: $I_e = 202$ A, Note: Rated operational current at an operating frequency of 4 kHz and an ambient air temperature of +40 °C, Note: Overload cycle for 60 s every 600 s, Assigned motor rating Note: for normal internally and externally ventilated 4 pole, three-phase asynchronous motors with 1500 rpm-1 at 50 Hz or 1800 min-1 at 60 Hz , Overload cycle for 60 s every 600 s, at 400 V, 50 Hz, Assigned motor rating 150 % Overload: $P = 110$ kW, 150 % Overload: $I_M = 196$ A, Assigned motor rating Note: at 440 - 480 V, 60 Hz, Assigned motor rating 150 % Overload: $P = 150$ HP, Assigned motor rating 150 % Overload: $I_M = 180$ A, Degree of Protection: IP55/NEMA 12, Interface/field bus (built-in): OP-Bus (RS485)/Modbus RTU, CANopen®, Fieldbus connection (optional): Ethernet IP, DeviceNet, PROFIBUS, PROFINET, Modbus-TCP, EtherCAT, SmartWire-DT, Fitted with: Radio interference suppression filter, Brake chopper, Additional PCB protection, OLED display,....

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Power XL Frequency Converters

Additional Product Information

General specifications

Product Name Eaton DA1 Variable frequency drive Catalog Number 169405 Model Code DA1-34202FB-B55C EAN

4015081658459 Product Length/Depth 341 mm Product Height 1280 mm Product Width 330 mm Product Weight 80 kg

Certifications UL Category Control No.: NMMS, NMMS7

RCM

Safety: EN 61800-5-1: 2003

CE

IEC/EN 61800-3

UL

IEC/EN61800-3

RoHS, ISO 9001

CSA-C22.2 No. 14

EAC

CUL

UL File No.: E172143

Specification for general requirements: IEC/EN 61800-2

Certified by UL for use in Canada

DNV

UL report applies to both US and Canada

IEC/EN61800-5

UL 508C

UkrSEPRO Catalog Notes The brake resistors are assigned based on the maximum rated power of the variable frequency drive. Additional brake resistors and designs (e.g. different duty cycles) are available upon request. General

Cable length 100 m, screened, maximum permissible, Motor feeder

200 m, screened, with motor choke, maximum permissible, Motor feeder

150 m, unscreened, maximum permissible, Motor feeder

C2 ≤ 5 m, Radio interference level, maximum motor cable length

C3 ≤ 25 m, Radio interference level, maximum motor cable length

300 m, unscreened, with motor choke, maximum permissible, Motor feeder Communication interface Ethernet IP, optional

PROFIBUS, optional

Modbus-TCP, optional

OP-Bus (RS485), built in

CANopen®, built in

EtherCAT, optional

Modbus RTU, built in

SmartWire-DT, optional

DeviceNet, optional

PROFINET, optional Connection to SmartWire-DT Yes

In conjunction with DX-NET-SWD1 SmartWire DT module Degree o...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DA1-34202FB-B55C with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.