

INDUSTRIAL COMPONENT DATA

DA1-34240FB-B55C 169407 Y7-169407 EATON ELECTRIC

Variable frequency drive, 400 V AC, 3-phase, 240 A, 132 kW,..

Brand: EATON - MOELLER | Manufacturer Part Number: DA1-34240FB-B55C



Manufacturer	EATON - MOELLER
MPN / Reference	DA1-34240FB-B55C
Catalog number	Y7-169407
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-D59516343D
Generated	2026-08-04

Product Overview

Variable frequency drive, 400 V AC, 3-phase, 240 A, 132 kW, IP55/NEMA 12, Radio interference suppression filter, OLED display, DC link choke

DA1-34240FB-B55C

Variable frequency drive, Part group reference (e.g. DIL): DA1, Rated operational voltage: $U_e = 400 \text{ V AC}$, 3-phase, 480 V AC, 3-phase, Output voltage with V_e : $U_2 = 400 \text{ V AC}$, 3-phase, 480 V AC, 3-phase, Mains voltage (50/60Hz): $U_{LN} = 380 (-10\%) - 480 (+10\%) \text{ V}$, Rated operational current At 150% overload: $I_e = 240 \text{ A}$, Note: Rated operational current at an operating frequency of 4 kHz and an ambient air temperature of +40 °C, Note: Overload cycle for 60 s every 600 s, Assigned motor rating Note: for normal internally and externally ventilated 4 pole, three-phase asynchronous motors with 1500 rpm-1 at 50 Hz or 1800 min-1 at 60 Hz , Overload cycle for 60 s every 600 s, at 400 V, 50 Hz, Assigned motor rating 150 % Overload: $P = 132 \text{ kW}$, 150 % Overload: $I_M = 231 \text{ A}$, Assigned motor rating Note: at 440 - 480 V, 60 Hz, Assigned motor rating 150 % Overload: $P = 200 \text{ HP}$, Assigned motor rating 150 % Overload: $I_M = 240 \text{ A}$, Degree of Protection: IP55/NEMA 12, Interface/field bus (built-in): OP-Bus (RS485)/Modbus RTU, CANopen®, Fieldbus connection (optional): Ethernet IP, DeviceNet, PROFIBUS, PROFINET, Modbus-TCP, EtherCAT, SmartWire-DT, Fitted with: Radio interference suppression filter, Brake chopper, Additional PCB protection, OLED display,....

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Power XL Frequency Converters**

Additional Product Information

General specifications

Product Name Eaton DA1 Variable frequency drive Catalog Number 169407 Model Code DA1-34240FB-B55C EAN

4015081658473 Product Length/Depth 341 mm Product Height 1280 mm Product Width 330 mm Product Weight 80 kg

Certifications RoHS, ISO 9001

Specification for general requirements: IEC/EN 61800-2

EAC

IEC/EN61800-3

RCM

UL 508C

UL File No.: E172143

IEC/EN 61800-3

UkrSEPRO

Certified by UL for use in Canada

CSA-C22.2 No. 14

IEC/EN61800-5

UL

CUL

Safety: EN 61800-5-1: 2003

UL Category Control No.: NMMS, NMMS7

CE

UL report applies to both US and Canada

DNV Catalog Notes The brake resistors are assigned based on the maximum rated power of the variable frequency drive.

Additional brake resistors and designs (e.g. different duty cycles) are available upon request. General

Cable length C2 ≤ 5 m, Radio interference level, maximum motor cable length

C3 ≤ 25 m, Radio interference level, maximum motor cable length

150 m, unscreened, maximum permissible, Motor feeder

200 m, screened, with motor choke, maximum permissible, Motor feeder

300 m, unscreened, with motor choke, maximum permissible, Motor feeder

100 m, screened, maximum permissible, Motor feeder Communication interface OP-Bus (RS485), built in

DeviceNet, optional

Modbus-TCP, optional

PROFIBUS, optional

Modbus RTU, built in

PROFINET, optional

Ethernet IP, optional

EtherCAT, optional

SmartWire-DT, optional

CANopen®, built in Connection to SmartWire-DT In conjunction with DX-NET-SWD1 SmartWire DT module

Yes Degree o...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DA1-34240FB-B55C with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.