

INDUSTRIAL COMPONENT DATA

SPX007A1-4A1B1 125660 Y7-125660 EATON ELECTRIC

Variable frequency drive, 400 V AC, 3-phase, 5.5 kW, IP21, Ra..

Brand: EATON - MOELLER | Manufacturer Part Number: SPX007A1-4A1B1



Manufacturer	EATON - MOELLER
MPN / Reference	SPX007A1-4A1B1
Catalog number	Y7-125660
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-A879A4A694
Generated	2026-08-05

Product Overview

Variable frequency drive, 400 V AC, 3-phase, 5.5 kW, IP21, Radio interference suppression filter, Brake chopper, OLED display, DC link choke, FR5

SPX007A1-4A1B1

Variable frequency drive, Part group reference (e.g. DIL): SPX, Rated operational voltage: $U_e = 400$ V AC, 3-phase, 480 V AC, 3-phase, 500 V AC, 3-phase, Output voltage with V_e : $U_2 = 400$ V AC, 3-phase, 480 V AC, 3-phase, 500 V AC, 3-phase, Mains voltage (50/60Hz): $U_{LN} = 380$ (-15%) - 500 (+10%) V, Rated operational current At 150% overload: $I_e = 12$ A, Rated operational current At 110% overload: $I_e = 16$ A, Note: Overload cycle for 60 s every 600 s, Assigned motor rating Note: For AC motors with internal and external ventilation with 50 Hz / 60 Hz, Overload cycle for 60 s every 600 s, at 400 V, 50 Hz, Assigned motor rating 150 % Overload: $P = 5.5$ kW, 110 % Overload: $P = 7.5$ kW, 150 % Overload: $I_M = 11.3$ A, 110 % Overload: $I_M = 15.2$ A, Assigned motor rating Note: at 440 - 480 V, 60 Hz, Assigned motor rating 150 % Overload: $P = 7.5$ HP, 110 % Overload: $P = 10$ HP, Assigned motor rating 150 % Overload: $I_M = 11$ A, 110 % Overload: $I_M = 14$ A, Degree of Protection: IP21, Fieldbus connection (optional): PROFIBUS-DP, LonWorks, CANopen®, DeviceNet, Modbus-TCP, BACnet/IP, Fitted with: Radio interference suppression filter, Brake chopper, OLED display, DC link choke, Frame size: FR5, Standards: Specification for general requirements: I...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Eaton Frequency Converters

Additional Product Information

General specifications

Product Name Eaton SPX variable frequency drive Catalog Number 125660 Model Code SPX007A1-4A1B1 EAN

4015081232703 Product Length/Depth 419 mm Product Height 214 mm Product Width 144 mm Product Weight 8.1 kg

Certifications UL 508C

CE

CUL

Specification for general requirements: IEC/EN 61800-2

IEC/EN 61800-3

IEC/EN61800-5

IEC/EN61800-3

UL File No.: E134360

RCM

Safety: EN 61800-5-1: 2003

DNV

UL Category Control No.: NMMS, NMMS2, NMMS7, NMMS8

RoHS, ISO 9001

UL

UL report applies to both US and Canada

CSA Class No.: 3211-06

CSA-C22.2 No. 14

Certified by UL for use in Canada General

Degree of protection IP21

NEMA Other Electromagnetic compatibility 1st and 2nd environments (according to EN 61800-3) Fitted with: DC link choke

Radio interference suppression filter

OLED display

Brake chopper

Internal DC link

IGBT inverter Frame size FR5 Mounting position Vertical Product Category Variable frequency drives Protection Finger and back-of-hand proof, Protection against direct contact (BGV A3, VBG4) Radio interference class C2, C3: depending on the motor cable length, the connected load, and ambient conditions. External radio interference suppression filters (optional) may be necessary. Suitable for Branch circuits, (UL/CSA) Climatic environmental conditions

Altitude Above 1000 m with 1 % performance reduction per 100 m

Max. 1000 m

Max. 3000 m Ambient operating temperature - min -10 °C Ambient operating temperature - max 50 °C Ambient operating temperature at 150% ove...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SPX007A1-4A1B1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.