

INDUSTRIAL COMPONENT DATA

SPX007A2-4A1B1 125260 Y7-125260 EATON ELECTRIC

Variable frequency drive SPX 3-/3-phase 480 V 5.5 kW dynamic ..

Brand: EATON - MOELLER | Manufacturer Part Number: SPX007A2-4A1B1



Manufacturer	EATON - MOELLER
MPN / Reference	SPX007A2-4A1B1
Catalog number	Y7-125260
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-CFB1611FDD
Generated	2026-08-05

Product Overview

Variable frequency drive SPX 3-/3-phase 480 V 5.5 kW ; dynamic vector control; protection type IP54; integrated EMC filter and braking transistor

Frequency converter. High performance. 16 A. 7.5 kW. IP54. 400 V

Variable frequency drive, 400 V AC, 3-phase, 5.5 kW, IP54, Radio interference suppression filter, Brake chopper, FR5

Variable frequency drive, Part group reference (e.g. DIL): SPX, Rated operational voltage: Ue = 400 V AC, 3-phase, 480 V AC, 3-phase, 500 V AC, 3-phase, Output voltage with Ve: U2 = 400 V AC, 3-phase, 480 V AC, 3-phase, 500 V AC,

3-phase, Mains voltage (50/60Hz): ULN = 380 (-15%) - 500 (+10%) V, Rated operational current At 150% overload: Ie = 12 A, Rated operational current At 110% overload: Ie = 16 A, Note: Overload cycle for 60 s every 600 s, Assigned motor rating

Note: For AC motors with internal and external ventilation with 50 Hz / 60 Hz, Overload cycle for 60 s every 600 s, at 400 V, 50 Hz , Assigned motor rating 150 % Overload: P = 5.5 kW, 110 % Overload: P = 7.5 kW, 150 % Overload: IM = 11.3 A,

110 % Overload: IM = 15.2 A, Assigned motor rating Note: at 440 - 480 V, 60 Hz, Assigned motor rating 150 % Overload: P = 7.5 HP, 110 % Overload: P = 10 HP, Assigned motor rating 150 % Overload: IM = 11 A, 110 % Overload: IM = 14 A,

Degree of Protection: IP54, Fitted with: Radio interference suppression filter, Brake chopper, Frame size: FR5, Standards: EM...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Eaton Frequency Converters
--------------	--

Additional Product Information

General specifications

Product Name Eaton SPX variable frequency drive Catalog Number 125260 Model Code SPX007A2-4A1B1 EAN

4015081228669 Product Length/Depth 419 mm Product Height 214 mm Product Width 144 mm Product Weight 8.1 kg

Certifications RCM

IEC/EN 61800-3

UL

UL 508C

CUL

RoHS, ISO 9001

CSA Class No.: 3211-06

CE

IEC/EN61800-3

Safety: EN 61800-5-1: 2003

UL Category Control No.: NMMS, NMMS2, NMMS7. NMMS8

UL report applies to both US and Canada

Certified by UL for use in Canada

CSA-C22.2 No. 14

IEC/EN61800-5

UL File No.: E134360 General

Degree of protection IP54

NEMA Other Electromagnetic compatibility 1st and 2nd environments (according to EN 61800-3) Fitted with: Radio interference suppression filter

Internal DC link

IGBT inverter

Brake chopper Frame size FR5 Mounting position Vertical Product Category Variable frequency drives Protection Finger and back-of-hand proof, Protection against direct contact (BGV A3, VBG4) Radio interference class C2, C3: depending on the motor cable length, the connected load, and ambient conditions. External radio interference suppression filters (optional) may be necessary. Suitable for Branch circuits, (UL/CSA) Climatic environmental conditions

Altitude Max. 1000 m

Max. 3000 m

Above 1000 m with 1 % performance reduction per 100 m Ambient operating temperature - min -10 °C Ambient operating temperature - max 40 °C Ambient operating temperature at 150% overload - min -10 °C Ambient operating temperature at 150% overload - max 40 °C Ambient....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SPX007A2-4A1B1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.