

INDUSTRIAL COMPONENT DATA

SPX040A2-4A1N1 125325 Y7-125325 EATON ELECTRIC

Variable frequency drive, 400 V AC, 3-phase, 30 kW, IP54, Rad..

Brand: EATON - MOELLER | Manufacturer Part Number: SPX040A2-4A1N1



Manufacturer	EATON - MOELLER
MPN / Reference	SPX040A2-4A1N1
Catalog number	Y7-125325
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-E2426198CB
Generated	2026-08-05

Product Overview

Variable frequency drive, 400 V AC, 3-phase, 30 kW, IP54, Radio interference suppression filter, OLED display, DC link choke, FR7

Frequency converter. High performance. 72 A. 37 kW. IP54. 400 V AC.

Variable frequency drive, Part group reference (e.g. DIL): SPX, Rated operational voltage: Ue = 400 V AC, 3-phase, 480 V AC, 3-phase, 500 V AC, 3-phase, Output voltage with Ve: U2 = 400 V AC, 3-phase, 480 V AC, 3-phase, 500 V AC, 3-phase, Mains voltage (50/60Hz): ULN = 380 (-15%) - 500 (+10%) V, Rated operational current At 150% overload: Ie = 61 A, Rated operational current At 110% overload: Ie = 72 A, Note: Overload cycle for 60 s every 600 s, Assigned motor rating Note: For AC motors with internal and external ventilation with 50 Hz / 60 Hz, Overload cycle for 60 s every 600 s, at 400 V, 50 Hz , Assigned motor rating 150 % Overload: P = 30 kW, 110 % Overload: P = 37 kW, 150 % Overload: IM = 55 A, 110 % Overload: IM = 68 A, Assigned motor rating Note: at 440 - 480 V, 60 Hz, Assigned motor rating 150 % Overload: P = 40 HP, 110 % Overload: P = 50 HP, Assigned motor rating 150 % Overload: IM = 40 A, 110 % Overload: IM = 65 A, Degree of Protection: IP54, Fieldbus connection (optional): PROFIBUS-DP, LonWorks, CANopen®, DeviceNet, Modbus-TCP, BACnet/IP, Fitted with: Radio interference suppression filter, OLED display, DC link choke, Frame size: FR7, Standards: Specification for general...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Eaton Frequency Converters**

Additional Product Information

General specifications

Product Name Eaton SPX variable frequency drive Catalog Number 125325 Model Code SPX040A2-4A1N1 EAN 4015081229314 Product Length/Depth 640 mm Product Height 257 mm Product Width 237 mm Product Weight 35 kg

Certifications UL report applies to both US and Canada

IEC/EN 61800-3

UL 508C

CSA-C22.2 No. 14

UL

UL Category Control No.: NMMS, NMMS2, NMMS7, NMMS8

UL File No.: E134360

IEC/EN61800-5

RCM

Specification for general requirements: IEC/EN 61800-2

Certified by UL for use in Canada

CSA Class No.: 3211-06

CE

IEC/EN61800-3

RoHS, ISO 9001

CUL

DNV

Safety: EN 61800-5-1: 2003 General

Degree of protection IP54

NEMA Other Electromagnetic compatibility 1st and 2nd environments (according to EN 61800-3) Fitted with: Radio interference suppression filter

Internal DC link

DC link choke

IGBT inverter

OLED display Frame size FR7 Mounting position Vertical Product Category Variable frequency drives Protection Finger and back-of-hand proof, Protection against direct contact (BGV A3, VBG4) Radio interference class C2, C3: depending on the motor cable length, the connected load, and ambient conditions. External radio interference suppression filters (optional) may be necessary. Suitable for Branch circuits, (UL/CSA) Climatic environmental conditions

Altitude Max. 1000 m

Above 1000 m with 1 % performance reduction per 100 m

Max. 3000 m Ambient operating temperature - min -10 °C Ambient operating temperature - max 50 °C Ambient operating temperature at 150% overload - min -10...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SPX040A2-4A1N1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.