

INDUSTRIAL COMPONENT DATA

SPX125A2-5A4B1 129597 Y7-129597 EATON ELECTRIC

Variable frequency drive, 600 V AC, 3-phase, 110 kW, IP54, Ra..

Brand: EATON - MOELLER | Manufacturer Part Number: SPX125A2-5A4B1



Manufacturer	EATON - MOELLER
MPN / Reference	SPX125A2-5A4B1
Catalog number	Y7-129597
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-DDDB4E5CCB
Generated	2026-08-03

Product Overview

Variable frequency drive, 600 V AC, 3-phase, 110 kW, IP54, Radio interference suppression filter, Brake chopper, OLED display, DC link choke, FR9

Frequency converter. High performance. 144 A. 132 kW. IP54. 690 V

Variable frequency drive, Part group reference (e.g. DIL): SPX, Rated operational voltage: $U_e = 600 \text{ V AC}$, 3-phase, 690 V AC, 3-phase, Output voltage with V_e : $U_2 = 600 \text{ V AC}$, 3-phase, 690 V AC, 3-phase, Mains voltage (50/60Hz): $U_{LN} = 525 (-15\%) - 690 (\pm 10\%) \text{ V}$, Rated operational current At 150% overload: $I_e = 125 \text{ A}$, Rated operational current At 110% overload: $I_e = 144 \text{ A}$, Note: Overload cycle for 60 s every 600 s, Assigned motor rating Note: For AC motors with internal and external ventilation with 50 Hz / 60 Hz, Overload cycle for 60 s every 600 s, at 690 V, 50 Hz, Assigned motor rating 150 % Overload: $P = 110 \text{ kW}$, 110 % Overload: $P = 132 \text{ kW}$, 150 % Overload: $I_M = 114 \text{ A}$, 110 % Overload: $I_M = 134 \text{ A}$, Assigned motor rating Note: at 690 V, 60 Hz, Assigned motor rating 150 % Overload: $P = 125 \text{ HP}$, 110 % Overload: $P = 150 \text{ HP}$, Assigned motor rating 150 % Overload: $I_M = 109 \text{ A}$, 110 % Overload: $I_M = 125 \text{ A}$, Degree of Protection: IP54, Fieldbus connection (optional): PROFIBUS-DP, LonWorks, CANopen®, DeviceNet, Modbus-TCP, BACnet/IP, Fitted with: Radio interference suppression filter, Brake chopper, OLED display, DC link choke, Frame size: FR9, Standards: Specification for general requi...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Eaton Frequency Converters
--------------	--

Additional Product Information

Variable frequency drive, 600 V AC, 3-phase, 110 kW, IP54, Radio interference suppression filter, Brake chopper, OLED display, FR9Variable frequency drive, Part group reference (e.g. DIL): SPX, Rated operational voltage: Ue = 600 V AC, 3-phase, 690 V AC, 3-phase, Output voltage with Ve: U2 = 600 V AC, 3-phase, 690 V AC, 3-phase, Mains voltage (50/60Hz): ULN = 525 (-15%) - 690 ($\pm 10\%$) V, Rated operational current At 150% overload: Ie = 125 A, Rated operational current At 110% overload: Ie = 144 A, Note: Overload cycle for 60 s every 600 s, Assigned motor rating Note: For AC motors with internal and external ventilation with 50 Hz / 60 Hz, Overload cycle for 60 s every 600 s, at 690 V, 50 Hz, Assigned motor rating 150 % Overload: P = 110 kW, 110 % Overload: P = 132 kW, 150 % Overload: IM = 114 A, 110 % Overload: IM = 134 A, Assigned motor rating Note: at 690 V, 60 Hz, Assigned motor rating 150 % Overload: P = 125 HP, 110 % Overload: P = 150 HP, Assigned motor rating 150 % Overload: IM = 109 A, 110 % Overload: IM = 125 A, Degree of Protection: IP54, Fieldbus connection (optional): PROFIBUS-DP, LonWorks, CANopen®, DeviceNet, Modbus-TCP, BACnet/IP, Fitted with: Radio interference suppression filter, Brake chopper, OLED display, DC link choke, Frame size: FR9, Standards: Specification for general requirements: IEC/EN 61800-2, EMC requirements: IEC/EN 61800-3, Safety requirements: IEC/EN 61800-5-1Delivery program

Product rangeVariable frequency drivesPart group reference (e.g. DIL)S...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SPX125A2-5A4B1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.