

INDUSTRIAL COMPONENT DATA

SPX150A1-4A1N1 125381 Y7-125381 EATON ELECTRIC

Variable frequency drive, 400 V AC, 3-phase, 110 kW, IP21, Ra..

Brand: EATON - MOELLER | Manufacturer Part Number: SPX150A1-4A1N1



Manufacturer	EATON - MOELLER
MPN / Reference	SPX150A1-4A1N1
Catalog number	Y7-125381
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-D9B63BFC54
Generated	2026-08-03

Product Overview

Variable frequency drive, 400 V AC, 3-phase, 110 kW, IP21, Radio interference suppression filter, OLED display, DC link choke, FR9

SPX150A1-4A1N1

Variable frequency drive, Part group reference (e.g. DIL): SPX, Rated operational voltage: $U_e = 400 \text{ V AC}$, 3-phase, 480 V AC, 3-phase, 500 V AC, 3-phase, Output voltage with V_e : $U_2 = 400 \text{ V AC}$, 3-phase, 480 V AC, 3-phase, 500 V AC, 3-phase, Mains voltage (50/60Hz): $U_{LN} = 380 (-15\%) - 500 (+10\%) \text{ V}$, Rated operational current At 150% overload: $I_e = 205 \text{ A}$, Rated operational current At 110% overload: $I_e = 261 \text{ A}$, Note: Overload cycle for 60 s every 600 s, Assigned motor rating Note: For AC motors with internal and external ventilation with 50 Hz / 60 Hz, Overload cycle for 60 s every 600 s, at 400 V, 50 Hz, Assigned motor rating 150 % Overload: $P = 110 \text{ kW}$, 110 % Overload: $P = 132 \text{ kW}$, 150 % Overload: $I_M = 196 \text{ A}$, 110 % Overload: $I_M = 231 \text{ A}$, Assigned motor rating Note: at 440 - 480 V, 60 Hz, Assigned motor rating 150 % Overload: $P = 150 \text{ HP}$, 110 % Overload: $P = 200 \text{ HP}$, Assigned motor rating 150 % Overload: $I_M = 150 \text{ A}$, 110 % Overload: $I_M = 240 \text{ A}$, Degree of Protection: IP21, Fieldbus connection (optional): PROFIBUS-DP, LonWorks, CANopen®, DeviceNet, Modbus-TCP, BACnet/IP, Fitted with: Radio interference suppression filter, OLED display, DC link choke, Frame size: FR9, Standards: Specification for general requirements: IEC/EN 61800-2, EMC require...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Eaton Frequency Converters**

Additional Product Information

Variable frequency drive, 400 V AC, 3-phase, 110 kW, IP21, Radio interference suppression filter, OLED display, FR9Variable frequency drive, Part group reference (e.g. DIL): SPX, Rated operational voltage: $U_e = 400 \text{ V AC}$, 3-phase, 480 V AC, 3-phase, 500 V AC, 3-phase, Output voltage with V_e : $U_2 = 400 \text{ V AC}$, 3-phase, 480 V AC, 3-phase, 500 V AC, 3-phase, Mains voltage (50/60Hz): $U_{LN} = 380 (-15\%) - 500 (+10\%) \text{ V}$, Rated operational current At 150% overload: $I_e = 205 \text{ A}$, Rated operational current At 110% overload: $I_e = 261 \text{ A}$, Note: Overload cycle for 60 s every 600 s, Assigned motor rating Note: For AC motors with internal and external ventilation with 50 Hz / 60 Hz, Overload cycle for 60 s every 600 s, at 400 V, 50 Hz, Assigned motor rating 150 % Overload: $P = 110 \text{ kW}$, 110 % Overload: $P = 132 \text{ kW}$, 150 % Overload: $I_M = 196 \text{ A}$, 110 % Overload: $I_M = 231 \text{ A}$, Assigned motor rating Note: at 440 - 480 V, 60 Hz, Assigned motor rating 150 % Overload: $P = 150 \text{ HP}$, 110 % Overload: $P = 200 \text{ HP}$, Assigned motor rating 150 % Overload: $I_M = 150 \text{ A}$, 110 % Overload: $I_M = 240 \text{ A}$, Degree of Protection: IP21, Fieldbus connection (optional): PROFIBUS-DP, LonWorks, CANopen®, DeviceNet, Modbus-TCP, BACnet/IP, Fitted with: Radio interference suppression filter, OLED display, DC link choke, Frame size: FR9, Standards: Specification for general requirements: IEC/EN 61800-2, EMC requirements: IEC/EN 61800-3, Safety requirements: IEC/EN 61800-5-1

General specificationsProduct nameEaton SPX variable frequency drivePa...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SPX150A1-4A1N1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.