

INDUSTRIAL COMPONENT DATA

SPX200A0-5A2N1 129600 EATON ELECTRIC Variable frequency drive SVX 3-/3-phase 200 kW 690 V degree of protecti..

Brand: EATON - MOELLER | Manufacturer Part Number: SPX200A0-5A2N1



Manufacturer	EATON - MOELLER
MPN / Reference	SPX200A0-5A2N1
Catalog number	129600
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-2BCBC55775
Generated	2026-08-05

Product Overview

Variable frequency drive SVX 3-/3-phase 200 kW 690 V; degree of protection IP00; integrated EMC filter

Frequency converter; High performance; 261 A; 250 kW; IP00; 690 V AC

Variable frequency drive, 600 V AC, 3-phase, 200 kW, IP00, OLED display, FR10

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Eaton Frequency Converters

Additional Product Information

Variable frequency drive, 600 V AC, 3-phase, 200 kW, IP00, OLED display, FR10Variable frequency drive, Part group reference (e.g. DIL): SPX, Rated operational voltage: $U_e = 600 \text{ V AC}$, 3-phase, 690 V AC, 3-phase, Output voltage with V_e : $U_2 = 600 \text{ V AC}$, 3-phase, 690 V AC, 3-phase, Mains voltage (50/60Hz): $U_{LN} = 525 (-15\%) - 690 (\pm 10\%) \text{ V}$, Rated operational current At 150% overload: $I_e = 208 \text{ A}$, Rated operational current At 110% overload: $I_e = 261 \text{ A}$, Note: Overload cycle for 60 s every 600 s, Assigned motor rating Note: For AC motors with internal and external ventilation with 50 Hz / 60 Hz, Overload cycle for 60 s every 600 s, at 690 V, 50 Hz, Assigned motor rating 150 % Overload: $P = 200 \text{ kW}$, 110 % Overload: $P = 250 \text{ kW}$, 150 % Overload: $I_M = 202 \text{ A}$, 110 % Overload: $I_M = 253 \text{ A}$, Assigned motor rating Note: at 690 V, 60 Hz, Assigned motor rating 150 % Overload: $P = 200 \text{ HP}$, 110 % Overload: $P = 300 \text{ HP}$, Assigned motor rating 150 % Overload: $I_M = 167 \text{ A}$, 110 % Overload: $I_M = 251 \text{ A}$, Degree of Protection: IP00, Fieldbus connection (optional): PROFIBUS-DP, LonWorks, CANopen®, DeviceNet, Modbus-TCP, BACnet/IP, Fitted with: OLED display, Frame size: FR10, Standards: Specification for general requirements: IEC/EN 61800-2, EMC requirements: IEC/EN 61800-3, Safety

requirements: IEC/EN 61800-5-1Delivery program

Product rangeVariable frequency drivesPart group reference (e.g. DIL)SPXRated operational voltage [Ue]600 V AC, 3-phase

690 V AC, 3-phaseOutput voltage with Ve[U2]600 V AC, 3-phase

690 V AC,....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SPX200A0-5A2N1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.