

## INDUSTRIAL COMPONENT DATA

# SPX300A2-4A4N1 125419 Y7-125419 EATON ELECTRIC

## Variable frequency drive SPX 3-/3-phase 480 V 200 kW dynamic ..

Brand: EATON - MOELLER | Manufacturer Part Number: SPX300A2-4A4N1



|                 |                                    |
|-----------------|------------------------------------|
| Manufacturer    | EATON - MOELLER                    |
| MPN / Reference | SPX300A2-4A4N1                     |
| Catalog number  | Y7-125419                          |
| Category        | Frequency converter less than 1 kV |
| Minimum order   | 1 Pcs                              |
| Document ID     | EO-4124978462                      |
| Generated       | 2026-08-03                         |

### Product Overview

Variable frequency drive SPX 3-/3-phase 480 V 200 kW ; dynamic vector control; protection type IP54; integrated EMC filter; with input fuse

SPX300A2-4A4N1

Variable frequency drive, 400 V AC, 3-phase, 200 kW, IP54, Radio interference suppression filter, OLED display, FR10  
Variable frequency drive, Part group reference (e.g. DIL): SPX, Rated operational voltage:  $U_e = 400 \text{ V AC}$ , 3-phase, 480 V AC, 3-phase, 500 V AC, 3-phase, Output voltage with  $V_e$ :  $U_2 = 400 \text{ V AC}$ , 3-phase, 480 V AC, 3-phase, 500 V AC, 3-phase, Mains voltage (50/60Hz):  $U_{LN} = 380 (-15\%) - 500 (+10\%) \text{ V}$ , Rated operational current At 150% overload:  $I_e = 385 \text{ A}$ , Rated operational current At 110% overload:  $I_e = 460 \text{ A}$ , Note: Overload cycle for 60 s every 600 s, Assigned motor rating Note: For AC motors with internal and external ventilation with 50 Hz / 60 Hz, Overload cycle for 60 s every 600 s, at 400 V, 50 Hz , Assigned motor rating 150 % Overload:  $P = 200 \text{ kW}$ , 110 % Overload:  $P = 250 \text{ kW}$ , 150 % Overload:  $I_M = 349 \text{ A}$ , 110 % Overload:  $I_M = 437 \text{ A}$ , Assigned motor rating Note: at 440 - 480 V, 60 Hz, Assigned motor rating 150 % Overload:  $P = 300 \text{ HP}$ , 110 % Overload:  $P = 350 \text{ HP}$ , Assigned motor rating 150 % Overload:  $I_M = 361 \text{ A}$ , 110 % Overload:  $I_M = 414 \text{ A}$ , Degree of Protection: IP54, Fieldbus connection (optional): PROFIBUS-DP, LonWorks, CANopen®, DeviceNet, Modbus-TCP, BACnet/IP, Fitted with: Radio interference suppression filter,...

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                                              |
|--------------|----------------------------------------------|
| Catalog path | EATON - MOELLER > Eaton Frequency Converters |
|--------------|----------------------------------------------|

## Additional Product Information

---

### General specifications

Product Name Eaton SPX variable frequency drive Catalog Number 125419 Model Code SPX300A2-4A4N1 EAN

4015081230259 Product Length/Depth 602 mm Product Height 2020 mm Product Width 595 mm Product Weight 275 kg

Certifications CE

Safety: EN 61800-5-1: 2003

RCM

UL File No.: E134360

Certified by UL for use in Canada

CUL

DNV

Specification for general requirements: IEC/EN 61800-2

UL 508C

UL Category Control No.: NMMS, NMMS2, NMMS7, NMMS8

CSA-C22.2 No. 14

IEC/EN 61800-3

IEC/EN61800-5

CSA Class No.: 3211-06

IEC/EN61800-3

RoHS, ISO 9001

UL

UL report applies to both US and Canada General

Degree of protection IP54

NEMA 12 Electromagnetic compatibility 1st and 2nd environments (according to EN 61800-3) Fitted with: Radio interference suppression filter

DC link choke

OLED display

Internal DC link

PC connection

Control unit

IGBT inverter Frame size FR10 Functions 4-quadrant operation possible Mounting position Vertical Product Category

Variable frequency drives Protection Finger and back-of-hand proof, Protection against direct contact (BGV A3, VBG4)

Radio interference class C2, C3: depending on the motor cable length, the connected load, and ambient conditions.

External radio interference suppression filters (optional) may be necessary. Suitable for Branch circuits, (UL/CSA) Climatic environmental conditions

Altitude Above 1000 m with 1 % performance reduction per 100 m

Max. 3000 m

Max. 1000 m Ambient operating temperature - min -10 °C Ambient operating temperature -...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SPX300A2-4A4N1 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.