

INDUSTRIAL COMPONENT DATA

SPX700A0-4A2N1 125459 Y7-125459 EATON ELECTRIC

Variable frequency drive SVX 3-/3-phase 500 kW 480 V degree O..

Brand: EATON - MOELLER | Manufacturer Part Number: SPX700A0-4A2N1



Manufacturer	EATON - MOELLER
MPN / Reference	SPX700A0-4A2N1
Catalog number	Y7-125459
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-68C25B54E5
Generated	2026-08-05

Product Overview

Variable frequency drive SVX 3-/3-phase 500 kW 480 V; degree of protection IP00; integrated EMC filter
SPX700A0-4A2N1

Variable frequency drive, 400 V AC, 3-phase, 500 kW, IP00, OLED display, FR12

Variable frequency drive, Part group reference (e.g. DIL): SPX, Rated operational voltage: $U_e = 400 \text{ V AC}$, 3-phase, 480 V AC, 3-phase, 500 V AC, 3-phase, Output voltage with V_e : $U_2 = 400 \text{ V AC}$, 3-phase, 480 V AC, 3-phase, 500 V AC, 3-phase, Mains voltage (50/60Hz): $U_{LN} = 380 (-15\%) - 500 (+10\%) \text{ V}$, Rated operational current At 150% overload: $I_e = 920 \text{ A}$, Rated operational current At 110% overload: $I_e = 1030 \text{ A}$, Note: Overload cycle for 60 s every 600 s, Assigned motor rating Note: For AC motors with internal and external ventilation with 50 Hz / 60 Hz, Overload cycle for 60 s every 600 s, at 400 V, 50 Hz, Assigned motor rating 150 % Overload: $P = 500 \text{ kW}$, 110 % Overload: $P = 560 \text{ kW}$, Assigned motor rating Note: at 440 - 480 V, 60 Hz, Assigned motor rating 150 % Overload: $P = 700 \text{ HP}$, 110 % Overload: $P = 800 \text{ HP}$, Degree of Protection: IP00, Fieldbus connection (optional): PROFIBUS-DP, LonWorks, CANopen®, DeviceNet, Modbus-TCP, BACnet/IP, Fitted with: OLED display, Frame size: FR12, Standards: Specification for general requirements: IEC/EN 61800-2, EMC requirements: IEC/EN 61800-3, Safety requirements: IEC/EN 61800-5-1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Eaton Frequency Converters
--------------	--

Additional Product Information

Variable frequency drive, 400 V AC, 3-phase, 500 kW, IP00, OLED display, FR12Variable frequency drive, Part group

reference (e.g. DIL): SPX, Rated operational voltage: $U_e = 400 \text{ V AC}$, 3-phase, 480 V AC , 3-phase, 500 V AC , 3-phase, Output voltage with V_e : $U_2 = 400 \text{ V AC}$, 3-phase, 480 V AC , 3-phase, 500 V AC , 3-phase, Mains voltage (50/60Hz): $U_{LN} = 380 (-15\%) - 500 (+10\%) \text{ V}$, Rated operational current At 150% overload: $I_e = 920 \text{ A}$, Rated operational current At 110% overload: $I_e = 1030 \text{ A}$, Note: Overload cycle for 60 s every 600 s, Assigned motor rating Note: For AC motors with internal and external ventilation with 50 Hz / 60 Hz, Overload cycle for 60 s every 600 s, at 400 V, 50 Hz, Assigned motor rating 150 % Overload: $P = 500 \text{ kW}$, 110 % Overload: $P = 560 \text{ kW}$, Assigned motor rating Note: at 440 - 480 V, 60 Hz, Assigned motor rating 150 % Overload: $P = 700 \text{ HP}$, 110 % Overload: $P = 800 \text{ HP}$, Degree of Protection: IP00, Fieldbus connection (optional): PROFIBUS-DP, LonWorks, CANopen®, DeviceNet, Modbus-TCP, BACnet/IP, Fitted with: OLED display, Frame size: FR12, Standards: Specification for general requirements: IEC/EN 61800-2, EMC requirements: IEC/EN 61800-3, Safety requirements: IEC/EN 61800-5-1

General specifications Product name Eaton SPX variable frequency drive Part

no. SPX700A0-4A2N1 EAN4015081230655 Product Length/Depth 115 millimetre Product height 36.2 millimetre Product

width 96 millimetre Product weight 550 kilogram Certifications RoHS, ISO 9001

IEC/EN 61800-3

Safety: EN 61800-5-1: 2003

UL....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SPX700A0-4A2N1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.