

INDUSTRIAL COMPONENT DATA

M22-RJ45-SA 107413 Y7-107413 EATON ELECTRIC Front element, +bulkhead interface RJ45

Brand: EATON - MOELLER | Manufacturer Part Number: M22-RJ45-SA



Manufacturer	EATON - MOELLER
MPN / Reference	M22-RJ45-SA
Catalog number	Y7-107413
Category	Accessories/spare parts for command devices
Minimum order	1 Pcs
Document ID	EO-E04A6CCE5D
Generated	2026-08-03

Product Overview

Front element, +bulkhead interface RJ45

M22-RJ45-SA

Eaton Moeller® series M22 Bulkhead interface, RJ45 socket, 8/8, cat. 5e, Bezel: titanium

Bulkhead interface, General accessories, RJ45 socket, 8/8, cat. 5e, Degree of Protection: IP65 (with closed cover), IP20 (with plug connected), Bezel: titanium, Connection to SmartWire-DT: no, For use with: Front mounting, Number of poles: 8 pole

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Auxiliary Control and Signalling Elements**

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Accessory Bulkhead interface Catalog Number 107413 Model Code

M22-RJ45-SA EAN 4015081071517 Product Length/Depth 30 mm Product Height 30 mm Product Width 30 mm Product

Weight 0.014 kg Compliances CE Marked Certifications UL 508

CSA Std. C22.2 No. 142

IEC 6113-2

UL report applies to both US and Canada

Certified by UL for use in Canada

IEC/EN 6113-2

UL File No.: E330994

UL
CSA Class No.: none
CSA-C22.2 No. 142
UL Category Control No.: DUXR, DUXR7
CE Catalog Notes RJ45 socket, 8/8, cat. 5e Features & Functions
Bezel color Titanium Design RJ45 Material Titanium front ring Number of poles Eight-pole General
Accessory/spare part type Accessory Degree of protection IP65 (with closed cover)
IP20 (with plug connected)
NEMA 12 (with closed cover) Lifespan, mechanical 750 insertion cycles Limit value class 5 Mounting depth 70 mm Opening diameter 22.5 mm Climatic environmental conditions
Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Ambient storage temperature - min -25 °C Ambient storage temperature - max 80 °C Electrical rating
Insulation resistance $\geq 100 \text{ M}\Omega$ Nominal current 1500 A Nominal voltage - max 50 V Rated operational voltage 24 V AC
Resistance $< 30 \text{ m}\Omega$ (volume resistance) Communication
Connection to SmartWire-DT No Contacts
Contact material CuSn, gold-plated Contact type 1:1 Force for positive opening - min 0 N Design verification
Heat dissipation capacity Pdiss 0 W 10.2.2 Corro...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-RJ45-SA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.