

INDUSTRIAL COMPONENT DATA

M22-USB-SA-150 147543 Y7-147543 EATON ELECTRIC Front element, chrome, +USB 3.0 A/A, connection cable 1.5m

Brand: EATON - MOELLER | Manufacturer Part Number: M22-USB-SA-150

PRODUCT IMAGE\nNOT
AVAILABLE

Manufacturer	EATON - MOELLER
MPN / Reference	M22-USB-SA-150
Catalog number	Y7-147543
Category	Accessories/spare parts for command devices
Minimum order	1 Pcs
Document ID	EO-F0A2935238
Generated	2026-08-02

Product Overview

Front element, chrome, +USB 3.0 A/A, connection cable 1.5m

M22-USB-SA-150

Eaton Moeller® series M22 Bulkhead interface, 1.5 m, Prefabricated cable with permanently connected USB 3.0 Type A plug, Bezel: titanium

Bulkhead interface, General accessories, Prefabricated cable with permanently connected USB 3.0 Type A plug, Cable length: 1.5 m, Degree of Protection: IP65 (with closed cover), IP20 (with plug connected), Bezel: titanium, Connection to SmartWire-DT: no, For use with: Front mounting, Number of poles: 9

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Auxiliary Control and Signalling Elements**

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Accessory Bulkhead interface Catalog Number 147543 Model Code

M22-USB-SA-150 EAN 4015081439942 Product Length/Depth 120 mm Product Height 30 mm Product Width 120 mm

Product Weight 0.14 kg Certifications IEC/EN 6113-2

UL

UL 508

Certified by UL for use in Canada

CSA Class No.: none

UL Category Control No.: DUXR, DUXR7

CE

UL File No.: E330994

CSA-C22.2 No. 142

UL report applies to both US and Canada Catalog Notes Prefabricated cable with permanently connected USB 3.0 Type A plug Features & Functions

Bezel color Titanium Design USB 3.0 A Number of poles Nine-pole General

Accessory/spare part type Accessory Degree of protection IP65 (with closed cover)

IP20 (with plug connected)

NEMA 12 (with closed cover) Lifespan, mechanical 100 insertion cycles Limit value class 3 Mounting depth 70 mm Opening diameter 22.5 mm Used with Used for USB connection Climatic environmental conditions

Ambient operating temperature - min -20 °C Ambient operating temperature - max 70 °C Ambient storage temperature - min 25 °C Ambient storage temperature - max 80 °C Electrical rating

Insulation resistance ≥ 100 M Ω Nominal current 900 A Nominal voltage - max 30 V Rated operational voltage 5 V AC/DC

Resistance < 30 m Ω (volume resistance) Communication

Connection to SmartWire-DT No Data transfer rate 5 GBit/s, max. Contacts

Contact material CuSn, gold-plated Contact type 1:1 Force for positive opening - min 0 N Cable

Cable length 1.5 m Cable sheat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-USB-SA-150 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.