

INDUSTRIAL COMPONENT DATA

M22-USB-SA 107412 Y7-107412 EATON ELECTRIC Front element, USB 3.0 A/A, with connection cable 0.6m

Brand: EATON - MOELLER | Manufacturer Part Number: M22-USB-SA



Manufacturer	EATON - MOELLER
MPN / Reference	M22-USB-SA
Catalog number	Y7-107412
Category	Accessories/spare parts for command devices
Minimum order	1 Pcs
Document ID	EO-A1CFC6D846
Generated	2026-08-01

Product Overview

Front element, USB 3.0 A/A, with connection cable 0.6m

M22-USB-SA

Eaton Moeller® series M22 Bulkhead interface, 0.6 m, Prefabricated cable with permanently connected USB 3.0 Type A plug, Bezel: titanium

Bulkhead interface, General accessories, Prefabricated cable with permanently connected USB 3.0 Type A plug, Cable length: 0.6 m, Degree of Protection: IP65 (with closed cover), IP20 (with plug connected), Bezel: titanium, Connection to SmartWire-DT: no, For use with: Front mounting, Number of poles: 9

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Accessory Bulkhead interface Catalog Number 107412 Model Code

M22-USB-SA EAN 4015081071500 Product Length/Depth 120 mm Product Height 30 mm Product Width 120 mm Product

Weight 0.043 kg Compliances CE Marked Certifications UL 508

CSA Std. C22.2 No. 142

IEC 6113-2

CE

UL Category Control No.: DUXR, DUXR7

UL

Certified by UL for use in Canada

IEC/EN 6113-2

UL File No.: E330994

UL report applies to both US and Canada

CSA-C22.2 No. 142

CSA Class No.: none Catalog Notes Prefabricated cable with permanently connected USB 3.0 Type A plug Features & Functions

Bezel color Titanium Design USB 3.0 A Material Titanium front ring Number of poles Nine-pole General

Accessories Connection cable Accessory/spare part type Accessory Degree of protection IP20 (with plug connected) IP65 (with closed cover)

NEMA 12 (with closed cover) Lifespan, mechanical 100 insertion cycles Limit value class 3 Mounting depth 70 mm Opening diameter 22.5 mm Climatic environmental conditions

Ambient operating temperature - min -20 °C Ambient operating temperature - max 70 °C Ambient storage temperature - min 25 °C Ambient storage temperature - max 80 °C Electrical rating

Insulation resistance $\geq 100 \text{ M}\Omega$ Nominal current 900 A Nominal voltage - max 30 V Rated operational voltage 5 V AC/DC

Resistance $< 30 \text{ m}\Omega$ (volume resistance) Communication

Connection to SmartWire-DT No Data transfer rate 5 GBit/s, max. Contacts

Contact material CuSn, gold-plated Contact type....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-USB-SA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.