


INDUSTRIAL COMPONENT DATA

FS-SOND-ERSTBESTELLUNG-T0 225355 Y7-225355 EATON ELECTRIC Front plate, HxW 45x45mm, non-standard inscription..

Brand: EATON - MOELLER | Manufacturer Part Number: FS-SOND-ERSTBESTELLUNG-T0



Manufacturer	EATON - MOELLER
MPN / Reference	FS-SOND-ERSTBESTELLUNG-T0
Catalog number	Y7-225355
Category	Accessories/spare parts for low-voltage switch technology
Minimum order	1 Pcs
Document ID	EO-F05D355C4E
Generated	2026-08-06

Product Overview

Front plate, HxW=45x45mm, non-standard inscription, for T0

FS-SOND-ERSTBESTELLUNG-T0

Front plate, For use with T0, T3, P1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

Front plate, For use with T0, T3, P1Accessories to cam switches T/switch-disconnectors P according to IEC/EN60947-3, design general: insulating material-surface mounting enclosure , flush mounting, centre mounting, rear mounting IVS service distribution board mounting. The capable, robust, compact T cam switches are used in industry, handwork, and building services management. A variety of standard circuits are available for selection. Special customer-specific circuits are implemented as supplements. The possibilities are almost unlimited here. Comprehensive accessories complete the switch range and supplement application possibilities.Delivery program

Basic functionFront platesFunctionStandard front plateWith customized inscriptionFor use withT0, T3, P1For use with(for frame 48 x 48)Non-standard orderFirst orderDesign verification as per IEC/EN 61439

Technical data for design verificationRated operational current for specified heat dissipation [In]0 AHeat dissipation per pole, current-dependent [Pvid]0 WEquipment heat dissipation, current-dependent [Pvid]0 WStatic heat dissipation, non-current-dependent [Pvs]0 WHeat dissipation capacity [Pdiss]0 WOperating ambient temperature min.-25 °COperating

ambient temperature max. +50 °C IEC/EN 61439 design verification 10.2 Strength of materials and parts 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2 Strength of materials and parts 10.2.3.1 Verification of thermal stability of enclosures Meets the product stand...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FS-SOND-ERSTBESTELLUNG-T0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.