

INDUSTRIAL COMPONENT DATA

FUSE 1000A 690V 2/110 AR UC 170M5166 EATON ELECTRIC

Fuse-link, high speed, 1000 A, AC 690 V, DIN 2, 61 x 61 ..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 1000A 690V 2/110 AR UC



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 1000A 690V 2/110 AR UC
Catalog number	170M5166
Category	HRC fuse
Minimum order	3 Pcs
Document ID	EO-50F381892C
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 1000 A, AC 690 V, DIN 2, 61 x 61 x 108 mm, aR, DIN, IEC, single indicator, 110 mm centres
FUSE 1000A 690V 2/110 AR UC

Fuse, Fuse-link, high speed, 1000 A, AC 690 V, DIN 2, 61 x 61 x 108 mm, aR, DIN, IEC, single indicator, square body with centre-bolted tags (slotted), semiconductor protection, DIN 43653, IEC 60269-4, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann Series High speed fuses

Additional Product Information

Fuse-link, high speed, 1000 A, AC 690 V, 200 kA, DIN 2, 61 x 61 x 108 mm, aR, DIN, IEC, single indicator, 110 mm fixing centres
Fuse, Fuse-link, high speed, 1000 A, AC 690 V, DIN 2, 61 x 61 x 108 mm, aR, DIN, IEC, single indicator, square body with centre-bolted tags (slotted), semiconductor protection, DIN 43653, IEC 60269-4, Breaking Capacity 200 kA
Delivery program

Product range Fuse
Basic function Fuse-link
Field of application high speed
Rated current [I]_N 1000 A
Rated voltage AC 690 V
Construction size DIN 2
Size 61 x 61 x 108 mm
Utilization category aR
Status indicators single indicator
Description 110 mm fixing centres
Breaking Capacity 200 kA
Usable for size/application semiconductor protection
Standard/Approval DIN IEC
Shapes square body with centre-bolted tags (slotted)
Standards/Regulations DIN 43653 IEC 60269-4
Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ()
[AFZ800015])
Construction size Other
Rated current 1000 A
Rated voltage 690 V
Voltage type AC
Rated switching capacity 200

kAUtilization categoryaR (accompanied semiconductor protection)Type of fuse status indicatorTop fuse status indicatorInsulated metal gripping lugs (IMGL)No
ETIM for 170M5166 Circuit breakers and fuses (EC004556)
Feature Name
Feature Value
Fuse system according to IEC 60269 (EF017676)
Other
Fuse construction type according to IE...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 1000A 690V 2/110 AR UC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.