

INDUSTRIAL COMPONENT DATA

FUSE 100A 660V 0000/80 AR UR 170M0167 EATON ELECTRIC

Fuse-link, high speed, 100 A, AC 660 V, size 0000, 18 x..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 100A 660V 0000/80 AR UR



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 100A 660V 0000/80 AR UR
Catalog number	170M0167
Category	HRC fuse
Minimum order	10 Pcs
Document ID	EO-D5CCEF8919
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 100 A, AC 660 V, size 0000, 18 x 19 x 100 mm, aR, UL, visual indicator

FUSE 100A 660V 0000/80 AR UR

Fuse, Fuse-link, high speed, 100 A, AC 660 V, size 0000, 18 x 19 x 100 mm, aR, UL, visual indicator, square body with offset bolted tags (slotted), semiconductor protection, UL 248-13, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series High speed fuses
--------------	--

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed square body fuse Catalog Number 170M0167 EAN 5027590440578
UPC 051712815697 Product Length/Depth 140 mm Product Height 40 mm Product Width 102 mm Product Weight 52.5 g

Compliances CE

RoHS Compliant

EAC Certifications IEC 60269-4 Electrical data

Amperage Rating 100 A Voltage rating 660 V Voltage type AC Watt losses 18 W Breaking capacity 200 kA Class Class aR

Product specification

Fuse size 0000

ETIM for 170M0167 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)
Other
Fuse construction type according to IEC 60269 (EF015865)
0000
Type of current (EF000143)
AC
Rated voltage AC (EF007682)
660 V
Rated current (EF000227)
100 A
Utilization category according to IEC 60269 (EF002572)
aR (accompanied semiconductor protection)
Breaking capacity (EF005617)
200 kA
Colour code (EF000931)
None
Type of fuse status indicator (EF004473)
Top fuse status indicator
Power loss at rated current (EF012389)
18 W
Mounting holes (EF021553)
M8
Centre-to-centre distance of connections (EF021151)
87.6 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 100A 660V 0000/80 AR UR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.