

INDUSTRIAL COMPONENT DATA

FUSE 100A 690V 000F/70 AR UR 170M1517 EATON ELECTRIC

Fuse-link, high speed, 100 A, AC 690 V, size 000, 24 x ..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 100A 690V 000F/70 AR UR



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 100A 690V 000F/70 AR UR
Catalog number	170M1517
Category	HRC fuse
Minimum order	5 Pcs
Document ID	EO-DBD691DF85
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 100 A, AC 690 V, size 000, 24 x 36 x 96 mm, aR, IEC, visual indicator

FUSE 100A 690V 000F/70 AR UR

Fuse, Fuse-link, high speed, 100 A, AC 690 V, size 000, 24 x 36 x 96 mm, aR, IEC, visual indicator, square body with offset bolted tags, semiconductor protection, IEC 60269-4, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed square body fuse Catalog Number 170M1517 Model Code FUSE 100A 690V 000F/70 AR UR EAN 5027590441100 UPC 051712217132 Product Length/Depth 102 mm Product Height 40 mm

Product Width 140 mm Product Weight 124.2 g Compliances Contact factory

RoHS Compliant Electrical data

Amperage Rating 100 A Voltage rating 690 V Voltage type AC Watt losses 24 W Breaking capacity 200 kA Class Class aR

Product specification

Fuse size 000

ETIM for 170M1517 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

000

Type of current (EF000143)

AC

Rated voltage AC (EF007682)

690 V

Rated current (EF000227)

100 A

Utilization category according to IEC 60269 (EF002572)

aR (accompanied semiconductor protection)

Breaking capacity (EF005617)

200 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

Top fuse status indicator

Power loss at rated current (EF012389)

24 W

Mounting holes (EF021553)

M8

Centre-to-centre distance of connections (EF021151)

73.8 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 100A 690V 000F/70 AR UR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.