

INDUSTRIAL COMPONENT DATA

FUSE 10A 660V 0000/80 GR UR 170M0158 EATON ELECTRIC

Fuse-link, high speed, 10 A, AC 660 V, size 0000, 18 x 1..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 10A 660V 0000/80 GR UR



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 10A 660V 0000/80 GR UR
Catalog number	170M0158
Category	HRC fuse
Minimum order	10 Pcs
Document ID	EO-F27BED7FAE
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 10 A, AC 660 V, size 0000, 18 x 19 x 100 mm, gR, UL, visual indicator
cartridge fuse, ultra fast, 10 A, AC 660 V, size 0000, 18 x 19 x 100 mm, gR, UL, visual indicator
Fuse, Fuse-link, high speed, 10 A, AC 660 V, size 0000, 18 x 19 x 100 mm, gR, UL, visual indicator, square body with offset bolted tags (slotted), semiconductor protection, UL 248-13, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series High speed fuses
--------------	--

Additional Product Information

Fuse-link, high speed, 10 A, AC 660 V, 200 kA, size 0000, 18 x 19 x 100 mm, gR, UL, visual indicator
Fuse, Fuse-link, high speed, 10 A, AC 660 V, size 0000, 18 x 19 x 100 mm, gR, UL, visual indicator, square body with offset bolted tags (slotted), semiconductor protection, UL 248-13, Breaking Capacity 200 kA
Delivery program

Product range Fuse
Basic function Fuse-link
Field of application high speed
Rated current [I]_N 10 A
Rated voltage AC 660 V
Construction size size 0000
Size 18 x 19 x 100 mm
Utilization category gR
Status indicator visual indicator
Breaking Capacity 200 kA
Usable for size/applications semiconductor protection
Standard/Approval UL
Shapes square body with offset bolted tags (slotted)
Standards/Regulations UL 248-13
Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ()
[AFZ800015])
Construction size Other
Rated current 10 A
Rated voltage 660 V
Voltage type AC
Rated switching capacity 200 kA
Utilization category gR (general purpose semiconductor protection)
Type of fuse status indicator Top fuse status indicator
Insulated metal gripping lugs (IMGL) No

ETIM for 170M0158 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse construction type according to IEC 60269 (EF015865)

Other

Rated current (EF000227)

10 A

Utilization category according to IEC 60269 (EF002572)

gR (general purpose semiconduct...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 10A 660V 0000/80 GR UR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.