

INDUSTRIAL COMPONENT DATA

FUSE 125A 690V 1*EK/76 AR UC 170M3363 EATON ELECTRIC

Fuse-link, high speed, 125 A, AC 690 V, compact size 1,..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 125A 690V 1*EK/76 AR UC



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 125A 690V 1*EK/76 AR UC
Catalog number	170M3363
Category	Low Voltage HRC fuse
Minimum order	3 Pcs
Document ID	EO-B1F62D3903
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 125 A, AC 690 V, compact size 1, 45 x 59 x 102 mm, aR, IEC, UL, single indicator

FUSE 125A 690V 1*EK/76 AR UC

Fuse-link, high speed, 125 A, AC 690 V, 200 kA, compact size 1, 45 x 59 x 102 mm, aR, IEC, UL, type K indicator, french style

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series High speed fuses
--------------	--

Additional Product Information

Fuse-link, high speed, 125 A, AC 690 V, 200 kA, compact size 1, 45 x 59 x 102 mm, aR, IEC, UL, type K indicator, french style
Fuse, Fuse-link, high speed, 125 A, AC 690 V, compact size 1, 45 x 59 x 102 mm, aR, IEC, UL, single indicator, square body with centre-bolted tags (slotted), french style, indicator style K for microswitch, semiconductor protection, IEC 60269-4, Breaking Capacity 200 kA
Delivery program

Product range Fuse Basic function Fuse-link Field of application high speed Rated current [I]_n 125 A Rated voltage AC 690

V Construction size compact size 1 Size 45 x 59 x 102 mm Utilization category aR Status indicator type K

indicator Description french style Breaking Capacity 200 kA Usable for size/applications semiconductor

protection Standard/Approval IEC

UL Shapes square body with centre-bolted tags (slotted) Standards/Regulations IEC 60269-4 Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process

control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ()

[AFZ800015]) Construction size Other Rated current 125 A Rated voltage 690 V Voltage type AC Rated switching capacity 200

kAUtilization categoryaR (accompanied semiconductor protection)Type of fuse status indicatorOtherInsulated metal gripping lugs (IMGL)No

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 125A 690V 1*EK/76 AR UC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.