

INDUSTRIAL COMPONENT DATA

FUSE 125A 690V 1 FU 78 AR UC 170M3613 EATON ELECTRIC

Fuse-link, high speed, 125 A, AC 690 V, compact size 1,..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 125A 690V 1 FU 78 AR UC



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 125A 690V 1 FU 78 AR UC
Catalog number	170M3613
Category	HRC fuse
Minimum order	6 Pcs
Document ID	EO-F3D7977492
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 125 A, AC 690 V, compact size 1, 45 x 45 x 110 mm, aR, IEC, UL

FUSE 125A 690V 1 FU 78 AR UC

Fuse, Fuse-link, high speed, 125 A, AC 690 V, compact size 1, 45 x 45 x 110 mm, aR, IEC, UL, square body with centre-bolted tags, US style, semiconductor protection, IEC 60269-4, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series High speed fuses
--------------	--

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed square body fuse Catalog Number 170M3613 EAN 5027590448642
UPC 051712792257 Product Length/Depth 305 mm Product Height 65 mm Product Width 145 mm Product Weight 319 g
Compliances CE Marked

RoHS Compliant Certifications UL Recognized

IEC Rated Electrical data

Amperage Rating 125 A Voltage rating 690 V Voltage type AC Clearing (I2T) 3700 at 660 V Pre arc (I2T) 550 Watt losses
26 W Breaking capacity 200 kA Class Class aR Product specification

Fuse size 1

ETIM for 170M3613 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)
Other
Fuse construction type according to IEC 60269 (EF015865)
1
Type of current (EF000143)
AC
Rated voltage AC (EF007682)
690 V
Rated current (EF000227)
125 A
Utilization category according to IEC 60269 (EF002572)
aR (accompanied semiconductor protection)
Breaking capacity (EF005617)
200 kA
Colour code (EF000931)
None
Type of fuse status indicator (EF004473)
None
Power loss at rated current (EF012389)
26 W
Mounting holes (EF021553)
M10
Centre-to-centre distance of connections (EF021151)
78.5 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 125A 690V 1 FU 78 AR UC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.