

INDUSTRIAL COMPONENT DATA

FUSE 1400A 750VDC A3/A131 P2C GR 170M2019 EATON

ELECTRIC Fuse-link, high speed, 1400 A, DC 750 V, size 23, 9..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 1400A 750VDC A3/A131 P2C GR



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 1400A 750VDC A3/A131 P2C GR
Catalog number	170M2019
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-A1A8333821
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 1400 A, DC 750 V, size 23, 92 x 148 x 161 mm, gR, IEC, single indicator

FUSE 1400A 750VDC A3/A131 P2C GR

Fuse, Fuse-link, high speed, 1400 A, DC 750 V, size 23, 92 x 148 x 161 mm, gR, IEC, single indicator, square body with parallel bolted tags, dual-barrel, indicator style K for microswitch, traction, third rail, IEC 60269-4, Breaking Capacity 110 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Busmann Series High speed fuses
--------------	---

Additional Product Information

Fuse-link, high speed, 1400 A, DC 750 V, size 23, 92 x 148 x 161 mm, gR, IEC, single indicator Fuse, Fuse-link, high speed, 1400 A, DC 750 V, size 23, 92 x 148 x 161 mm, gR, IEC, single indicator, square body with parallel bolted tags, dual-barrel, indicator style K for microswitch, traction, third rail, IEC 60269-4, Breaking Capacity 110 kA [Delivery program Product range Fuse Basic function Fuse-link Field of application high speed Rated current [I] 1400 A Rated voltage DC 750 V Construction size size 23 Size 92 x 148 x 161 mm Utilization category gR Status indicator single indicator Description dual-barrel

indicator style K for microswitch Breaking Capacity 110 kA usable for size/applications traction

third rail Standard/Approval IEC Shape square body with parallel bolted tags Standards/Regulations IEC 60269-4 , Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ()

[AFZ800015]) Construction size Other Rated current 1400 A Rated voltage 750 V Voltage type DC Voltage type DC Rated

switching capacity 110 kA Utilization category gR (general purpose semiconductor protection) Type of fuse status indicator

Other Insulated metal gripping lugs (IMGL) No]

ETIM for 170M2019 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse construction type according to IEC 60269...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 1400A 750VDC A3/A131 P2C GR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.