

INDUSTRIAL COMPONENT DATA

FUSE 1500A 690V 3FKE/90 AR UC 170M6668 EATON

ELECTRIC Fuse-link, high speed, 1500 A, AC 690 V, size 3, 76 X ..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 1500A 690V 3FKE/90 AR UC



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 1500A 690V 3FKE/90 AR UC
Catalog number	170M6668
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-612959605C
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 1500 A, AC 690 V, size 3, 76 x 92 x 135 mm, aR, IEC, UL, single indicator

FUSE 1500A 690V 3FKE/90 AR UC

Fuse, Fuse-link, high speed, 1500 A, AC 690 V, size 3, 76 x 92 x 135 mm, aR, IEC, UL, single indicator, square body with centre-bolted tags, US style, indicator style K for microswitch, semiconductor protection, IEC 60269-4, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed square body fuse Catalog Number 170M6668 EAN 5996516020357
UPC 051712265072 Product Length/Depth 168 mm Product Height 76 mm Product Width 95 mm Product Weight 998 g

Compliances CE Marked

RoHS Compliant Certifications UL Recognized

IEC Rated Product specifications

Type Fuse Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers Amperage Rating 1500 A
Breaking capacity 200 kA Fuse indicator Centre fuse status indicator Insulated metal gripping lugs (IMGL) No Utilization
category aR (accompanied semiconductor protection) Voltage type AC Fuse size 3 Rated voltage AC 690 V

Center-to-center distance of connections 91 mm Current type AC Mounting dimension Other Class Class aR Clearing (I2T)
3100000 at 660 V Watt losses 160 W Fuse shape Square body, center bolted tags Pre arc (I2T) 460000 Color None
Interrupt rating 200 kAIC Fitted with: Type K Indicator for micro Connection Blade end x blade end Construction size 3
Packaging type Standard Voltage rating 690 V Fuse type US Style
FKE/Type K indicator for micro
Bolted tag Fuse system (according to IEC 60269) Other
ETIM for 170M6668 Circuit breakers and fuses (EC004556)
Feature Name
Feature Value
Fuse system according to IEC 60269 (EF017676)
Other
Fuse construction type according to IEC 60269 (EF015865)
3
Type of current (EF000143)
AC
Rated voltage AC (EF007682)
690 V
Rated current (EF000227)
1500 A
Utilization category according to IEC 6026...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 1500A 690V 3FKE/90 AR UC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.