

INDUSTRIAL COMPONENT DATA

FUSE 1500A 750VDC A3/A131 P2C GR 170M2020 EATON

ELECTRIC Fuse-link, high speed, 1500 A, DC 750 V, size 23, 9..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 1500A 750VDC A3/A131 P2C GR



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 1500A 750VDC A3/A131 P2C GR
Catalog number	170M2020
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-A313C271A9
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 1500 A, DC 750 V, size 23, 92 x 148 x 161 mm, gR, IEC, single indicator

FUSE 1500A 750VDC A3/A131 P2C GR

Fuse-link, high speed, 1500 A, DC 750 V, 110 kA, size 23, 92 x 148 x 161 mm, gR, IEC, type K indicator, dual-barrel

Fuse, Fuse-link, high speed, 1500 A, DC 750 V, size 23, 92 x 148 x 161 mm, gR, IEC, single indicator, square body with parallel bolted tags, dual-barrel, indicator style K for microswitch, traction, third rail, IEC 60269-4, Breaking Capacity 110 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Busmann Series High speed fuses
--------------	---

Additional Product Information

Fuse-link, high speed, 1500 A, DC 750 V, 110 kA, size 23, 92 x 148 x 161 mm, gR, IEC, type K indicator, dual-barrel

Fuse-link, high speed, 1500 A, DC 750 V, size 23, 92 x 148 x 161 mm, gR, IEC, single indicator, square body with parallel

bolted tags, dual-barrel, indicator style K for microswitch, traction, third rail, IEC 60269-4, Breaking Capacity 110 kA
Delivery program

Product rangeFuseBasic functionFuse-linkField of applicationhigh speedRated current [I]1500 ARated voltageDC 750

VConstruction sizesize 23Size92 x 148 x 161 mmUtilization categorygRStatus indicatorK

indicatorDescriptiondual-barrelBreaking Capacity110 kAusable for size/applicationtraction

third railStandard/ApprovallIECShapesquare body with parallel bolted tagsStandards/RegulationsIEC 60269-4Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ()

[AFZ800015])Construction sizeOtherRated current1500 ARated voltage750 VVoltage typeDCRated switching capacity110 kAUtilization categorygR (general purpose semiconductor protection)Type of fuse status indicatorOtherInsulated metal gripping lugs (IMGL)No

ETIM for 170M2020 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

3

Type of current (E...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 1500A 750VDC A3/A131 P2C GR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.