

INDUSTRIAL COMPONENT DATA

FUSE 1750A 550V 3BKN/65 AR 170M6632 EATON ELECTRIC

Fuse-link, high speed, 1750 A, AC 550 V, size 3, 76 x 92 ..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 1750A 550V 3BKN/65 AR



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 1750A 550V 3BKN/65 AR
Catalog number	170M6632
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-7DE3D62DFC
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 1750 A, AC 550 V, size 3, 76 x 92 x 65 mm, aR, IEC, single indicator
fuse cartridge, ultra fast, 1750 A, AC 550 V, size 3, 76 x 92 x 65 mm, aR, IEC, single indicator
Fuse, Fuse-link, high speed, 1750 A, AC 550 V, size 3, 76 x 92 x 65 mm, aR, IEC, single indicator, square body with flush end contacts, indicator style K for microswitch, semiconductor protection, IEC 60269-4, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series High speed fuses
--------------	--

Additional Product Information

Fuse-link, high speed, 1750 A, AC 550 V, 200 kA, size 3, 76 x 92 x 65 mm, aR, IEC, type K indicator
Fuse, Fuse-link, high speed, 1750 A, AC 550 V, size 3, 76 x 92 x 65 mm, aR, IEC, single indicator, square body with flush end contacts, indicator style K for microswitch, semiconductor protection, IEC 60269-4, Breaking Capacity 200 kA
Delivery program
Product range Fuse
Basic function Fuse-link
Field of application high speed
Rated current [I]_N 1750 A
Rated voltage AC 550 V
Construction size size 3
Size 76 x 92 x 65 mm
Utilization category aR
Status indicator type K indicator
Breaking Capacity 200 kA
Usable for size/application semiconductor protection
Standard/Approval IEC
Shapes square body with flush end contacts
Standards/Regulations IEC 60269-4
Technical data ETIM 7.0
Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ()
[AFZ800015])
Construction size Other
Rated current 1750 A
Rated voltage 550 V
Voltage type AC
Rated switching capacity 200 kA
Utilization category aR (accompanied semiconductor protection)
Type of fuse status indicator Other
Insulated metal gripping lugs (IMGL) No

ETIM for 170M6632 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse construction type according to IEC 60269 (EF015865)

Other

Rated current (EF000227)

1750 A

Utilization category according to IEC 60269 (EF002572)

aR (accompanied semiconductor prote...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 1750A 550V 3BKN/65 AR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.