

INDUSTRIAL COMPONENT DATA

FUSE 2000A 600V 3SBKN/90 AR 170M6131 EATON ELECTRIC

Fuse-link, high speed, 2000 A, AC 600 V, size 3, 74 x 92..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 2000A 600V 3SBKN/90 AR



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 2000A 600V 3SBKN/90 AR
Catalog number	170M6131
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-43D6F5CF27
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 2000 A, AC 600 V, size 3, 74 x 92 x 90 mm, aR, IEC, single indicator

FUSE 2000A 600V 3SBKN/90 AR

Fuse, Fuse-link, high speed, 2000 A, AC 600 V, size 3, 74 x 92 x 90 mm, aR, IEC, single indicator, square body with flush end contacts, indicator style K for microswitch, Special type, semiconductor protection, IEC 60269-4

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed square body fuse Catalog Number 170M6131 EAN 5027590339131

Product Length/Depth 168 mm Product Height 76 mm Product Width 95 mm Product Weight 967 g Compliances CE

RoHS Compliant

EAC Certifications IEC 60269-4 Electrical data

Amperage Rating 2000 A Voltage rating 600 V Voltage type AC Watt losses 275 W Breaking capacity 100 kA Class Class

aR Product specification

Fuse size 3

ETIM for 170M6131 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

IEC 60269-4 flush end connections type A
Fuse construction type according to IEC 60269 (EF015865)
3
Type of current (EF000143)
AC
Rated voltage AC (EF007682)
600 V
Rated current (EF000227)
2000 A
Utilization category according to IEC 60269 (EF002572)
aR (accompanied semiconductor protection)
Breaking capacity (EF005617)
100 kA
Colour code (EF000931)
None
Type of fuse status indicator (EF004473)
Centre fuse status indicator
Power loss at rated current (EF012389)
275 W
Mounting holes (EF021553)
M12
Centre-to-centre distance of connections (EF021151)
88.8 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 2000A 600V 3SBKN/90 AR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.