

INDUSTRIAL COMPONENT DATA

FUSE 2000A 690V 4BN/65 AR UC 170M7062 EATON ELECTRIC

Fuse-link, high speed, 2000 A, AC 690 V, size 4, 67 x 1..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 2000A 690V 4BN/65 AR UC



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 2000A 690V 4BN/65 AR UC
Catalog number	170M7062
Category	HRC fuse
Minimum order	2 Pcs
Document ID	EO-FCAB78F4E5
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 2000 A, AC 690 V, size 4, 67 x 105 x 105 mm, aR, IEC, single indicator

FUSE 2000A 690V 4BN/65 AR UC

Fuse-link, 2000 A, AC 690 V, 200 kA, size 4, 67 x 105 x 105 mm, aR, IEC, single indicator

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series High speed fuses
--------------	--

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed square body fuse Catalog Number 170M7062 Model Code FUSE 2000A 690V 4BN/65 AR UC EAN 5027590463492 UPC 051712266468 Product Length/Depth 67 mm Product Height 105 mm Product Width 105 mm Product Weight 1843 g Compliances CE Marked

RoHS Compliant Certifications IEC Rated

UL Recognized Electrical data

Amperage Rating 2000 A Voltage rating 690 V, 700 V Voltage type AC Clearing (I₂T) 3950000 at 660 V Pre arc (I₂T) 600000 Watt losses 245 W Breaking capacity 200 kA Class Class aR Product specification

Fuse size 4

ETIM for 170M7062 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

4

Type of current (EF000143)

AC

Rated voltage AC (EF007682)

690 V

Rated current (EF000227)

2000 A

Utilization category according to IEC 60269 (EF002572)

aR (accompanied semiconductor protection)

Breaking capacity (EF005617)

200 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

Top fuse status indicator

Power loss at rated current (EF012389)

245 W

Mounting holes (EF021553)

M10

Centre-to-centre distance of connections (EF021151)

66.6 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 2000A 690V 4BN/65 AR UC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.