

## INDUSTRIAL COMPONENT DATA

# FUSE 200A 690V DIN 2 GR 170M5881 EATON ELECTRIC cartridge fuse, ultra fast, 200 A, AC 690 V, DIN 2, 60 x 74 ..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 200A 690V DIN 2 GR



|                 |                         |
|-----------------|-------------------------|
| Manufacturer    | EATON - MOELLER         |
| MPN / Reference | FUSE 200A 690V DIN 2 GR |
| Catalog number  | 170M5881                |
| Category        | HRC fuse                |
| Minimum order   | 3 Pcs                   |
| Document ID     | EO-76B672584F           |
| Generated       | 2026-08-06              |

## Product Overview

cartridge fuse, ultra fast, 200 A, AC 690 V, DIN 2, 60 x 74 x 150 mm, gR, DIN, IEC, simple indicator

FUSE 200A 690V DIN 2 GR

Fuse-link, high speed, 200 A, AC 690 V, 200 kA, DIN 2, 60 x 74 x 150 mm, gR, DIN, IEC, type T indicator, live gripping lugs

Fuse, Fuse-link, high speed, 200 A, AC 690 V, DIN 2, 60 x 74 x 150 mm, gR, DIN, IEC, single indicator, square body with knife blade contacts, live gripping lugs, indicator style T for microswitch, semiconductor protection, DIN 43620, IEC

60269-4, Breaking Capacity 200 kA

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                    |
|--------------|----------------------------------------------------|
| Catalog path | EATON - MOELLER > Bussmann Series High speed fuses |
|--------------|----------------------------------------------------|

## Additional Product Information

Fuse-link, high speed, 200 A, AC 690 V, 200 kA, DIN 2, 60 x 74 x 150 mm, gR, DIN, IEC, type T indicator, live gripping lugs

Fuse, Fuse-link, high speed, 200 A, AC 690 V, DIN 2, 60 x 74 x 150 mm, gR, DIN, IEC, single indicator, square body with knife blade contacts, live gripping lugs, indicator style T for microswitch, semiconductor protection, DIN 43620, IEC

60269-4, Breaking Capacity 200 kA

Delivery program

Product range Fuse Basic function Fuse-link Field of application high speed Rated current [I]<sub>n</sub> 200 A Rated voltage AC 690

V Construction size DIN 2 Size 60 x 74 x 150 mm Utilization category gR Status indicator type T indicator Description live gripping lugs Breaking Capacity 200 kA Usable for size/application semiconductor protection Standard/Approval DIN

IEC 60269-4 Shapes square body with knife blade contacts Standards/Regulations DIN 43620

IEC 60269-4 Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process

control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ([email protected]  
[AFZ800015])Construction sizeOtherRated current200 ARated voltage690 VVoltage typeACRated switching capacity200  
kAUtilization categorygR (general purpose semiconductor protection)Type of fuse status indicatorTop fuse status  
indicatorInsulated metal gripping lugs (IMGL)No  
ETIM for 170M5881 Circuit breakers and fuses (EC004556)  
Feature Name  
Feature Value  
Fuse system according to IEC 60269 (EF017676)  
Other  
Fuse....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 200A 690V DIN 2 GR with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use  
[electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd  
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification  
requirements against the manufacturer documentation before purchase or installation.