

INDUSTRIAL COMPONENT DATA

FUSE 20A 690V 000U/80 GR UC 170M1310 EATON ELECTRIC

Fuse-link, high speed, 20 A, AC 690 V, DIN 000, 21 x 40 ..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 20A 690V 000U/80 GR UC



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 20A 690V 000U/80 GR UC
Catalog number	170M1310
Category	HRC fuse
Minimum order	10 Pcs
Document ID	EO-C5965934AC
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 20 A, AC 690 V, DIN 000, 21 x 40 x 100 mm, gR, DIN, IEC

FUSE 20A 690V 000U/80 GR UC

Eaton Bussmann series high speed square body fuse, 690V, 20A, 200 kAIC, None, Fuse, Blade end X blade end, Class gR, DIN 43 620

Fuse, Fuse-link, high speed, 20 A, AC 690 V, DIN 000, 21 x 40 x 100 mm, gR, DIN, IEC, square body with offset bolted tags (slotted), semiconductor protection, DIN 43653, IEC 60269-4, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series High speed fuses
--------------	--

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed square body fuse Catalog Number 170M1310 Model Code FUSE 20A 690V 000U/80 GR UC EAN 5027590440714 UPC 051712216463 Product Length/Depth 105 mm Product Height 46 mm Product Width 300 mm Product Weight 134.5 g Compliances CE Marked

RoHS Compliant Certifications IEC Rated

UL Recognized Product specifications

Type Fuse Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers Amperage Rating 20 A Breaking capacity 200 kA Fuse indicator None Insulated metal gripping lugs (IMGL) No Utilization category gR (general purpose semiconductor protection) Voltage type AC Fuse size 000 Rated voltage AC 690 V Center-to-center distance of connections 76.7 mm Current type AC Mounting dimension M8 Class Class gR Clearing (I2T) 78 at 660 V Watt losses 7 W

Fuse shape Square body, slotted offset bolted tags Pre arc (I2T) 11.5 Color None Interrupt rating 200 kAIC Connection
Blade end x blade end Construction size 000 Packaging type Standard Voltage rating 690 V (IEC), 700 V (UL) Fuse type
DIN 43653

U/80 Without indicator

Bolted tag Fuse system (according to IEC 60269) Other

ETIM for 170M1310 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)
000

Type of current (EF000143)

AC

Rated voltage AC (EF007682)

690 V

Rated current (EF000227)

20 A

Utilization category according to IEC 60269 (EF00...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 20A 690V 000U/80 GR UC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.