

INDUSTRIAL COMPONENT DATA

FUSE 250A 2000VDC 2+/A173 DST AR 170M2041 EATON

ELECTRIC Fuse-link, high speed, 250 A, DC 2000 V, 65 x 89 x

..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 250A 2000VDC 2+/A173 DST AR



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 250A 2000VDC 2+/A173 DST AR
Catalog number	170M2041
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-BF659369C5
Generated	2026-08-05

Product Overview

FUSE 250A 2000VDC 2+/A173 DST AR

Fuse-link, high speed, 250 A, DC 2000 V, 65 x 89 x 213 mm, aR, IEC, with indicator

Fuse, Fuse-link, high speed, 250 A, DC 2000 V, 65 x 89 x 213 mm, aR, IEC, with indicator, square body with offset bolted tags, indicator style K for microswitch, traction, third rail, IEC 60269-4, Breaking Capacity 100 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed traction fuse Catalog Number 170M2041 EAN 5027590303811 Product Length/Depth 213 mm Product Height 89 mm Product Width 65 mm Product Weight 2082 g Certifications IEC 60269-4

Electrical data

Amperage Rating 250 A Voltage rating 2000 V Voltage type DC Clearing (I2T) 211000 at 2000 Vdc Pre arc (I2T) 21870 Watt losses 133 W Breaking capacity 100 kA Class Class aR Product specification

Fitted with: Double slot tags

ETIM for 170M2041 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)
Other
Fuse construction type according to IEC 60269 (EF015865)
Other
Type of current (EF000143)
DC
Rated voltage DC (EF012281)
2000 V
Rated current (EF000227)
250 A
Utilization category according to IEC 60269 (EF002572)
aR (accompanied semiconductor protection)
Breaking capacity (EF005617)
100 kA
Colour code (EF000931)
None
Type of fuse status indicator (EF004473)
Other
Power loss at rated current (EF012389)
133 W
Mounting holes (EF021553)
M8
Centre-to-centre distance of connections (EF021151)
194 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 250A 2000VDC 2+/A173 DST AR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.