

INDUSTRIAL COMPONENT DATA

FUSE 250A 690V 1*BN/50 AR UC 170M3416 EATON ELECTRIC Fuse-link, high speed, 250 A, AC 690 V, compact size 1,..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 250A 690V 1*BN/50 AR UC



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 250A 690V 1*BN/50 AR UC
Catalog number	170M3416
Category	HRC fuse
Minimum order	6 Pcs
Document ID	EO-83D3FCC6C3
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 250 A, AC 690 V, compact size 1, 45 x 59 x 51 mm, aR, IEC, UL, single indicator, flush end, M8
FUSE 250A 690V 1*BN/50 AR UC

Eaton Bussmann series high speed square body fuse, 700V (UL), 690 V (IEC), 250A, 200 kAIC, Top fuse status indicator, Fuse, Class aR, Flush

Fuse, Fuse-link, high speed, 250 A, AC 690 V, compact size 1, 45 x 59 x 51 mm, aR, IEC, UL, single indicator, square body with flush end contacts, semiconductor protection, IEC 60269-4, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series High speed fuses
--------------	--

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed square body fuse Catalog Number 170M3416 EAN 5027590447621

UPC 051712256025 Product Length/Depth 155 mm Product Height 45 mm Product Width 90 mm Product Weight

246.3333333 g Compliances CE Marked

RoHS Compliant Certifications UL Recognized

IEC Rated Electrical data

Amperage Rating 250 A Voltage rating 690 V Voltage type AC Clearing (I2T) 28500 at 660 V Pre arc (I2T) 4200 Watt losses 40 W Breaking capacity 200 kA Class Class aR Product specification

Fuse size 1*

ETIM for 170M3416 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

IEC 60269-4 flush end connections type A

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of current (EF000143)

AC

Rated voltage AC (EF007682)

690 V

Rated current (EF000227)

250 A

Utilization category according to IEC 60269 (EF002572)

aR (accompanied semiconductor protection)

Breaking capacity (EF005617)

200 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

Top fuse status indicator

Power loss at rated current (EF012389)

40 W

Mounting holes (EF021553)

M8

Centre-to-centre distance of connections (EF021151)

50 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 250A 690V 1*BN/50 AR UC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.