

INDUSTRIAL COMPONENT DATA

FUSE 25A 1200VDC 1C/A116 SST AR 170M2101 EATON

ELECTRIC Fuse-link, high speed, 25 A, DC 1200 V, compact size..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 25A 1200VDC 1C/A116 SST AR



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 25A 1200VDC 1C/A116 SST AR
Catalog number	170M2101
Category	HRC fuse
Minimum order	3 Pcs
Document ID	EO-8867C10A33
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 25 A, DC 1200 V, compact size 1, 39 x 66 x 164 mm, aR, IEC, single indicator

FUSE 25A 1200VDC 1C/A116 SST AR

Fuse, Fuse-link, high speed, 25 A, DC 1200 V, compact size 1, 39 x 66 x 164 mm, aR, IEC, single indicator, square body with offset bolted tags, indicator style K for microswitch, traction, third rail, IEC 60269-4, Breaking Capacity 50 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann Series High speed fuses

Additional Product Information

Fuse-link, high speed, 25 A, DC 1200 V, compact size 1, 39 x 66 x 164 mm, aR, IEC, single indicator Fuse, Fuse-link, high speed, 25 A, DC 1200 V, compact size 1, 39 x 66 x 164 mm, aR, IEC, single indicator, square body with offset bolted tags, indicator style K for microswitch, traction, third rail, IEC 60269-4, Breaking Capacity 50 kA [Delivery program

Product range Fuse Basic function Fuse-link Field of application high speed Rated current [I] 25 A Rated voltage DC 1200 V Construction size compact size 1 Size 39 x 66 x 164 mm Utilization category aR Status indicator single indicator Description indicator style K for microswitch Breaking Capacity 50 kA usable for size/applications traction

third rail Standard/Approval IEC Shape square body with offset bolted tags Standards/Regulations IEC 60269-4 , Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ()

[AFZ800015]) Construction size Other Rated current 25 A Rated voltage 1200 V Voltage type DC Voltage type DC Rated switching capacity 150 kA Utilization category aR (accompanied semiconductor protection) Type of fuse status indicator

Other Insulated metal gripping lugs (IMGL) No]

ETIM for 170M2101 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construct...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 25A 1200VDC 1C/A116 SST AR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.