

INDUSTRIAL COMPONENT DATA

FUSE 25A 690V 00/80 GR 170M2608 EATON ELECTRIC

Fuse-link, high speed, 25 A, AC 690 V, DIN 00, 30 x 51 x 100 ..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 25A 690V 00/80 GR



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 25A 690V 00/80 GR
Catalog number	170M2608
Category	HRC fuse
Minimum order	6 Pcs
Document ID	EO-6E97042F8E
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 25 A, AC 690 V, DIN 00, 30 x 51 x 100 mm, gR, DIN, IEC, single indicator

FUSE 25A 690V 00/80 GR

Eaton Bussmann series high speed square body fuse, 25 A, 690 V (IEC), 78 Millimeter, Size 0, Top fuse status indicator

Fuse, Fuse-link, high speed, 25 A, AC 690 V, DIN 00, 30 x 51 x 100 mm, gR, DIN, IEC, single indicator, square body with offset bolted tags (slotted), semiconductor protection, DIN 43653, IEC 60269-4, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed square body fuse Catalog Number 170M2608 Model Code FUSE 25A 690V 00/80 GR EAN 5027590442169 UPC 051712254076 Product Length/Depth 233 mm Product Height 66 mm Product Width 140 mm Product Weight 215 g Compliances CE Marked

RoHS Compliant Certifications UL Recognized

IEC Rated Product specifications

Type Fuse Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers Amperage Rating 25 A Breaking capacity 200 kA Fuse indicator Top fuse status indicator Insulated metal gripping lugs (IMGL) No Utilization category gR (general purpose semiconductor protection) Voltage type AC Fuse size 00 Rated voltage AC 690 V Center-to-center distance of connections 78 mm Current type AC Mounting dimension M10 Class Class gR Clearing (I2T) 130 at 660 V Watt losses 6 W Fuse shape Square body, slotted offset bolted tags Pre arc (I2T) 19 Color None Interrupt

rating 200 kAIC Connection Blade end x blade end Construction size 00 Packaging type Standard Voltage rating 690 V (IEC) Fuse type DIN 43653

/80 Visual indicator Fuse system (according to IEC 60269) Other

ETIM for 170M2608 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

00

Type of current (EF000143)

AC

Rated voltage AC (EF007682)

690 V

Rated current (EF000227)

25 A

Utilization category according to IEC 60269 (EF002572)

gR (genera...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 25A 690V 00/80 GR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.