

INDUSTRIAL COMPONENT DATA

FUSE 3000A 660V 4PKN/60 AR 170M7216 EATON ELECTRIC

Fuse-link, high speed, 3000 A, AC 660 V, size 4, 120 x 10..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 3000A 660V 4PKN/60 AR



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 3000A 660V 4PKN/60 AR
Catalog number	170M7216
Category	HRC fuse
Minimum order	2 Pcs
Document ID	EO-BC31F7EA29
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 3000 A, AC 660 V, size 4, 120 x 105 x 59 mm, aR, IEC, single indicator
fuse cartridge, ultra-fast, 3000 A, AC 660 V, size 4, 120 x 105 x 59 mm, aR, IEC, single indicator
FUSE 3000A 660V 4PKN/60 AR

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann Series High speed fuses

Additional Product Information

Fuse-link, high speed, 3000 A, AC 660 V, 200 kA, size 4, 120 x 105 x 59 mm, aR, IEC, type K indicator
Fuse, Fuse-link, high speed, 3000 A, AC 660 V, size 4, 120 x 105 x 59 mm, aR, IEC, single indicator, square body with press pack contacts, indicator style K for microswitch, Protection of power rectifiers, IEC 60269-4, Breaking Capacity 200 kA
Delivery program Product range Fuse Basic function Fuse-link Field of application high speed Rated current [I]
3000 A Rated voltage AC 660 V Construction size size 4 Size 120 x 105 x 59 mm Utilization category aR Status indicator type K indicator Breaking Capacity 200 kA
Usable for size/applications Protection of power rectifiers Standard/Approval IEC Shapes square body with press pack contacts Standards/Regulations IEC 60269-4 Technical data ETIM 7.0
Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ()
[AFZ800015]) Construction size Other Rated current 3000 A Rated voltage 660 V Voltage type AC Rated switching capacity kA Utilization category aR (accompanied semiconductor protection) Type of fuse status indicator Other Insulated metal gripping lugs (IMGL) No
ETIM for 170M7216 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse construction type according to IEC 60269 (EF015865)

Other

Rated current (EF000227)

3000 A

Utilization category according to IEC 60269 (EF002572)

aR (accompanied sem...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 3000A 660V 4PKN/60 AR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.