

INDUSTRIAL COMPONENT DATA

FUSE 315A 1000V 2TN/110 AR UR 170M5982 EATON

ELECTRIC Fuse-link, high speed, 315 A, AC 1000 V, DIN 2, 59 x 7..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 315A 1000V 2TN/110 AR UR



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 315A 1000V 2TN/110 AR UR
Catalog number	170M5982
Category	HRC fuse
Minimum order	3 Pcs
Document ID	EO-B6D89DA0FF
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 315 A, AC 1000 V, DIN 2, 59 x 75 x 138 mm, aR, DIN, IEC, single indicator

FUSE 315A 1000V 2TN/110 AR UR

Fuse, Fuse-link, high speed, 315 A, AC 1000 V, DIN 2, 59 x 75 x 138 mm, aR, DIN, IEC, single indicator, square body with centre-bolted tags (slotted), indicator style T for microswitch, semiconductor protection, DIN 43653, IEC 60269-4, Breaking Capacity 150 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann Series High speed fuses

Additional Product Information

Fuse-link, high speed, 315 A, AC 1000 V, 150 kA, DIN 2, 59 x 75 x 138 mm, aR, DIN, IEC, type T indicator
Fuse, Fuse-link, high speed, 315 A, AC 1000 V, DIN 2, 59 x 75 x 138 mm, aR, DIN, IEC, single indicator, square body with centre-bolted tags (slotted), indicator style T for microswitch, semiconductor protection, DIN 43653, IEC 60269-4, Breaking Capacity 150 kA
Delivery program

Product range Fuse
Basic function Fuse-link
Field of application high speed
Rated current [I]_N 315 A
Rated voltage AC 1000 V
Construction size DIN 2
Size 59 x 75 x 138 mm
Utilization category aR
Status indicator type T indicator
Breaking Capacity 150 kA
Usable for size/application semiconductor protection
Standard/Approval DIN IEC
Shapes square body with centre-bolted tags (slotted)
Standards/Regulations DIN 43653 IEC 60269-4
Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ( [AFZ800015]) Construction size Other Rated current 315 A Rated voltage 1000 V Voltage type AC Rated switching capacity 125 kA Utilization category aR (accompanied semiconductor protection) Type of fuse status indicator Top fuse status indicator Insulated metal gripping lugs (IMGL) No
ETIM for 170M5982 Circuit breakers and fuses (EC004556)
Feature Name
Feature Value
Fuse system according to IEC 60269 (EF017676)
Other
Fuse construction type according to IEC 60269 (EF015865)
2...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 315A 1000V 2TN/110 AR UR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.