

INDUSTRIAL COMPONENT DATA

FUSE 315A 1250V 3FKE/115 AR CU 170M6738 EATON

ELECTRIC Fuse-link, high speed, 315 A, AC 1250 V, size 3, 76 X..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 315A 1250V 3FKE/115 AR CU



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 315A 1250V 3FKE/115 AR CU
Catalog number	170M6738
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-7F7436535B
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 315 A, AC 1250 V, size 3, 76 x 92 x 159 mm, aR, IEC, UL, single indicator

FUSE 315A 1250V 3FKE/115 AR CU

Fuse, Fuse-link, high speed, 315 A, AC 1250 V, size 3, 76 x 92 x 159 mm, aR, IEC, UL, single indicator, square body with centre-bolted tags, US style, indicator style K for microswitch, semiconductor protection, IEC 60269-4, Breaking Capacity 100 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series High speed fuses
--------------	--

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed square body fuse Catalog Number 170M6738 EAN 5027590296311

UPC 051712265355 Product Length/Depth 168 mm Product Height 76 mm Product Width 95 mm Product Weight 1.298 g

Compliances CE

RoHS Compliant

EAC Certifications IEC 60269-4

UL Electrical data

Amperage Rating 315 A Voltage rating 1250 V Voltage type AC Clearing (I2T) 58000 at 1000 V, 77500 at 1250 V Pre arc (I2T) 9500 Watt losses 85 W Breaking capacity 100 kA Class Class aR Product specification

Fuse size 3 Fitted with: Type K Indicator for micro
ETIM for 170M6738 Circuit breakers and fuses (EC004556)
Feature Name
Feature Value
Fuse system according to IEC 60269 (EF017676)
Other
Fuse construction type according to IEC 60269 (EF015865)
3
Type of current (EF000143)
AC
Rated voltage AC (EF007682)
1250 V
Rated current (EF000227)
315 A
Utilization category according to IEC 60269 (EF002572)
aR (accompanied semiconductor protection)
Breaking capacity (EF005617)
100 kA
Colour code (EF000931)
None
Type of fuse status indicator (EF004473)
Centre fuse status indicator
Power loss at rated current (EF012389)
85 W
Mounting holes (EF021553)
Other
Centre-to-centre distance of connections (EF021151)
114 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 315A 1250V 3FKE/115 AR CU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.