

INDUSTRIAL COMPONENT DATA

FUSE 315A 2000VDC 2+/A173 DST AR 170M2042 EATON

ELECTRIC Fuse-link, high speed, 315 A, DC 2000 V, 65 x 89 x

..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 315A 2000VDC 2+/A173 DST AR



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 315A 2000VDC 2+/A173 DST AR
Catalog number	170M2042
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-45638CCE81
Generated	2026-08-06

Product Overview

FUSE 315A 2000VDC 2+/A173 DST AR

Fuse-link, high speed, 315 A, DC 2000 V, 100 kA, 65 x 89 x 213 mm, aR, IEC, type K indicator

Fuse, Fuse-link, high speed, 315 A, DC 2000 V, 65 x 89 x 213 mm, aR, IEC, with indicator, square body with offset bolted tags, indicator style K for microswitch, traction, third rail, IEC 60269-4, Breaking Capacity 100 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog pathEATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

Fuse-link, high speed, 315 A, DC 2000 V, 100 kA, 65 x 89 x 213 mm, aR, IEC, type K indicator
Fuse, Fuse-link, high speed, 315 A, DC 2000 V, 65 x 89 x 213 mm, aR, IEC, with indicator, square body with offset bolted tags, indicator style K for microswitch, traction, third rail, IEC 60269-4, Breaking Capacity 100 kA
Delivery program

Product rangeFuseBasic functionFuse-linkField of applicationhigh speedRated current [I]315 ARated voltageDC 2000 VSize65 x 89 x 213 mmUtilization categoryaRStatus indicatorstyle K indicatorBreaking Capacity100 kAusable for size/applicationtraction

third railStandard/ApprovalIECShapesquare body with offset bolted tagsStandards/RegulationsIEC 60269-4

ETIM for 170M2042 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of current (EF000143)

DC

Rated voltage DC (EF012281)

2000 V

Rated current (EF000227)

315 A

Utilization category according to IEC 60269 (EF002572)

aR (accompanied semiconductor protection)

Breaking capacity (EF005617)

100 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

Other

Power loss at rated current (EF012389)

158 W

Mounting holes (EF021553)

M8

Centre-to-centre distance of connections (EF021151)

194 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 315A 2000VDC 2+/A173 DST AR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.