

INDUSTRIAL COMPONENT DATA

FUSE 315A 690V 1*GN/50 AR UC 170M3517 EATON ELECTRIC FUSE 315A 690V 1*GN/50 AR UC

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 315A 690V 1*GN/50 AR UC



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 315A 690V 1*GN/50 AR UC
Catalog number	170M3517
Category	HRC fuse
Minimum order	6 Pcs
Document ID	EO-8D479742E7
Generated	2026-08-06

Product Overview

FUSE 315A 690V 1*GN/50 AR UC

Fuse-link, high speed, 315 A, AC 690 V, compact size 1, 45 x 45 x 140 mm, aR, UL, IEC, single indicator

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

Fuse-link, high speed, 315 A, AC 690 V, compact size 1, 45 x 45 x 140 mm, aR, UL, IEC, single indicator
Fuse-link, high speed, 315 A, AC 690 V, compact size 1, 45 x 59 x 51 mm, aR, IEC, UL, single indicator, square body with flush end contacts, US thread, semiconductor protection, IEC 60269-4, Breaking Capacity 200 kA
Delivery program

Product range Fuse Basic function Fuse-link Field of application high speed Rated current [I]_N 315 A Rated voltage AC 690

V Construction size compact size 1 Size 45 x 45 x 140 mm Utilization category aR Status indicator single indicator usable for size/applications DC common bus, DC drives, power converters/rectifiers Standard/Approval UL

IEC Shapes square body with flush end contacts Standards/Regulations UL Recognized

IEC Rated Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ()

[AFZ800015]) Construction size Other Rated current 315 A Rated voltage 690 V Voltage type Rated switching

capacity kA Utilization category aR (accompanied semiconductor protection) Type of fuse status indicator Top fuse status indicator Insulated metal gripping lugs (IMGL) No

ETIM for 170M3517 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of current (EF000143)

AC

Rated v...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 315A 690V 1*GN/50 AR UC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.