

INDUSTRIAL COMPONENT DATA

FUSE 315A 690V aR DIN 00 HSDNH 170M1572D EATON ELECTRIC cartridge fuse, ultra rapid, 315 A, AC 690 V, DIN 00..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 315A 690V aR DIN 00 HSDNH



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 315A 690V aR DIN 00 HSDNH
Catalog number	170M1572D
Category	HRC fuse
Minimum order	6 Pcs
Document ID	EO-471A5DD6DD
Generated	2026-08-06

Product Overview

cartridge fuse, ultra rapid, 315 A, AC 690 V, DIN 00, aR, DIN, IEC, indicator double, metal terminals

FUSE 315A 690V aR DIN 00 HSDNH

Fuse-link, high speed, 315 A, AC 690 V, 200 kA, DIN 00, aR, DIN, IEC, type T indicator, square body with knife blade contacts

Fuse, Fuse-link, high speed, 315 A, AC 690 V, DIN 00, aR, DIN, IEC, dual (combination) indicator system, square-body with knife blade contacts, live gripping lugs, indicator style T for microswitch, semiconductor protection, DIN 43620, IEC 60269-4, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed square body fuse Catalog Number 170M1572D EAN 5027590441421

UPC 051712334938 Product Length/Depth 79 mm Product Height 69 mm Product Width 30 mm Product Weight 204 g

Compliances CE Marked

RoHS Compliant Certifications UL Recognized

IEC Rated Electrical data

Amperage Rating 315 A Voltage rating 690 V (IEC), 700 V (UL) Voltage type AC Clearing (I2T) 84500 at 660 V Pre arc (I2T) 12000 Watt losses 45 W Breaking capacity 200 kA Class Class aR Product specification

Fuse size 00 Fitted with: Dual indicator

ETIM for 170M1572D Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

00

Type of current (EF000143)

AC

Rated voltage AC (EF007682)

690 V

Rated current (EF000227)

315 A

Utilization category according to IEC 60269 (EF002572)

aR (accompanied semiconductor protection)

Breaking capacity (EF005617)

200 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

Combination fuse status indicator

Power loss at rated current (EF012389)

45 W

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 315A 690V aR DIN 00 HSDNH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.